

EUROLITE Set 2x LED BAR-6 QCL RGBW + Soft Bag

2x Spotlight bar with 6 x 4 W 4in1 LED including soft bag

Art. No.: 20000404

GTIN: 4026397621037



Features:

- 6 LEDs 4 W high-power 4in1 RGBW (homogenous color mix)
 - Color change adjustable; Dimmer electronic; color blend stepless
 - Strobe effect
 - Can be operated in 2; 4; 5; 6; 9 CH mode
 - The device is cooled by passive convection cooling
 - Control via stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
 - Flicker-free
 - With a beam angle of 17°
 - With mounting bracket
 - 4 digit 7-segment LED display
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
 - Silent operation
 - Application possibility: Suspended; wall mounting
 - <p>EUROLITE SB-205 Soft Bag
- Universal softbag**
- Ideal for e.g. LED bars with 50 cm length and accessories
 - With divider
 - With 2 device compartments
 - High-quality workmanship with nylon , black
 - Interior with foam padding
 - 2 carrying straps

Logistic

EAN / GTIN: 4026397621037

Weight: 8,20 kg

Length: 0.61 m

Width: 0.31 m

Height: 0.42 m

Technical specifications:

Weight:	3.62 kg
---------	---------

EUROLITE LED BAR-6 QCL RGBW Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	15 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	6 x 4 W high-power 4in1 RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	33°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum casting; metal; plastic
Dimensions:	Length: 60 cm Depth: 6.5 cm Height: 10 cm
Weight:	1.66 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø7mm
Material:	Metal, 2 mm

Cable construction:	3 x 0.75 mm² H05VV-F
Cable length:	Approx. 1.1 m

EUROLITE SB-205 Soft Bag

Maximum load:	25 kg
Carrying strap:	2 pc/pcs
Material:	Nylon, water repellent
Color:	Black
Dimensions:	Width: 57.5 cm Depth: 17 cm Height: 12 cm
Weight:	0.30 kg

Scope of delivery:

- 1 x light effect
- 2 x mounting bracket
- 1 x power cord
- 2 x screw
- 2 x washer
- 1 x user manual