

EUROLITE Set 4x LED PIX-12 HCL + Controller

4x Spotlight bar with 12 x 10 W 6in1 LED including compact DMX controller

Art. No.: 20000408

GTIN:



Features:

- 12 LEDs 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
 LEDs controlled separately
- Color blend stepless; color change adjustable; Dimmer electronic
- Strobe effect; UV effect
- Can be operated in 4; 6; 16; 36; 74 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control
- Flicker-free
- With a beam angle of 20°
- With mounting bracket
- Mains input and output for power linking up to 8 units
- <p>EUROLITE DMX LED EASY Operator 4x6
- **Compact DMX controller for 4 LED spotlights with up to 6 colors each**
- DMX controller for standard LED spotlights
- Easy handling
- 4 fixtures with RGBAW+UV LEDs can be controlled individually or in combination
- DMX channels for red, green, blue, amber, white, UV and master
- Various modes for the DMX channel sequence selectable
- Manual control via 6 faders
- 2 faders for direct RGBW and A/UV mixing
- Adjustable strobe function
- Blackout function
- 8 integrated show programs
- Preprogrammed 8 scenes/chases
- Can transmit up to 28 DMX channels

Logistic

- Control via DMX; sound to light via microphone; stand-alone
- Desktop console housing
- For application areas such as: Party room; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation

Technical specifications:

Weight:	21.84 kg
---------	----------

EUROLITE LED PIX-12 HCL Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	12 x 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
DMX channels:	4; 6; 16; 36; 74
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control
Fixtures available for:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	41°
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 100 cm Depth: 11.5 cm Height: 16.5 cm
Weight:	5.20 kg
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

EUROLITE DMX LED EASY Operator 4x6

Power supply:	100-240 V AC, 50/60 Hz 9V DC 800 mA
Power consumption:	10 W
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Preprogrammed 8 scenes/chases
DMX channels:	Output 28
Control:	DMX; sound to light via microphone; stand-alone
Housing color:	Black
Color:	Black
Housing design:	Desktop console housing
Dimensions:	Width: 25 cm Depth: 11.5 cm Height: 5.5 cm
Weight:	1.04 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:

4 x EUROLITE LED PIX-12 HCL Bar

1 x spotlight
1 x user manual
1 x power cord
1 x remote control
1 x battery

1 x EUROLITE DMX LED EASY Operator 4x6

1 x controller
1 x user manual
1 x external mains adapter