

EUROLITE Set 4x LED PAR-56 HCL sil + Case + Controller

4x PAR-56 Spot with 9 x 10 W 6in1 LED including PRO flightcase and compact DMX controller

Art. No.: 20000410

GTIN:



The article is no longer in our assortment.

Features:

- Stepless color blend, color change, dimmer, strobe effect and UV effect
- 9 LEDs 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
- Strobe effect; UV effect
- Can be operated in 4; 6; 10 CH mode
- Control via stand-alone; DMX; sound to light via microphone; IR remote control
- Flicker-free
- With a beam angle of 20°
- With mounting bracket
- 4 digit 7-segment LED display
- Available in various colors
- <p>ROADINGER Flightcase EPS-56 4x PAR-56 Spot short

Trunk case

- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Closes with a
- For further information about this product, please refer to the Data Sheet under "Downloads"
- <p>EUROLITE DMX LED EASY Operator 4x6

Compact DMX controller for 4 LED spotlights with up to 6 colors each

- DMX controller for standard LED spotlights
- Easy handling
- 4 fixtures with RGBAW+UV LEDs can be controlled individually or in combination

Logistic

- DMX channels for red, green, blue, amber, white, UV and master
- Various modes for the DMX channel sequence selectable
- Manual control via 6 faders
- 2 faders for direct RGBW and A/UV mixing
- Adjustable strobe function
- Blackout function
- 8 integrated show programs
- Preprogrammed 8 scenes/chases
- Can transmit up to 28 DMX channels
- Control via DMX; sound to light via microphone; stand-alone
- Desktop console housing
- For application areas such as: Party room; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation

Technical specifications:

Weight:	16.14 kg
---------	----------

EUROLITE LED PAR-56 HCL Short sil

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	9 x 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
DMX channels:	4; 6; 10
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; sound to light via microphone; IR remote control
Fixtures available for:	Light´ J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; LED EASY OPERATOR 4x4; Light Captain
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	38°
Housing color:	Silver
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 20.5 cm Depth: 17.5 cm Height: 23 cm
Weight:	1.79 kg
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

ROADINGER Flightcase EPS-56 4x PAR-56 Spot short

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	22 cm x 22 cm x 24 cm
Inside dimensions:	44 cm x 44 cm x 24 cm
Dimensions:	Width: 48.5 cm Depth: 48.5 cm Height: 31 cm
Weight:	7.95 kg

EUROLITE DMX LED EASY Operator 4x6

Power supply:	100-240 V AC, 50/60 Hz 9V DC 800 mA
Power consumption:	10 W
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Preprogrammed 8 scenes/chases
DMX channels:	Output 28
Control:	DMX; sound to light via microphone; stand-alone
Housing color:	Black
Color:	Black
Housing design:	Desktop console housing
Dimensions:	Width: 25 cm Depth: 11.5 cm Height: 5.5 cm
Weight:	1.04 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:**4 x EUROLITE LED PAR-56 HCL Short sil**

1 x spotlight
1 x user manual
1 x power cord
1 x remote control
1 x battery

1 x EUROLITE DMX LED EASY Operator 4x6

1 x controller
1 x user manual
1 x external mains adapter