

## EUROLITE Set 4x AKKU Flat Light 1 silver + Soft Bag + Charger

4x flat spotlight with 15 W RGBW LED, soft bag and charger

Art. No.: 20000446

GTIN:



**The article is no longer in our assortment.**

### Features:

- With QuickDMX transceiver - cordless, flexible and versatile
  - Equipped with a 15 W QCL LED in red, green, blue and white
  - Cordless and versatile
  - Elegant housing for indoor use
  - With integrated QuickDMX transmitter/receiver for the wireless transmission of DMX512 signals
  - Operation via built-in rechargeable lithium-ion battery with up to 18 hours operating time
  - Integrated automatic charging of the battery with indicator
  - Stepless color blend, color change, preset colors, dimmer and strobe effect
  - Dimmer speed (step response) adjustable
  - Addressing and setting via Control Board with touch buttons and LCD
  - Inclination angle manually adjustable via the bracket
  - Charger included in delivery
  - 1 LED 15 W SMD 9080 4in1 RGBW (homogenous color mix)
  - Strobe effect
  - Can be operated in 3; 4; 6; 8; 10 CH mode
  - The device is cooled by passive convection cooling
  - Control via master/slave function; stand-alone; IR remote control; sound to light via microphone; QuickDMX
  - Flicker-free
  - With a beam angle of 8°
  - For application areas such as: Wedding/gala/events; small rental
  - Silent operation
- device**
- Cordless, flexible and versatile
  - Battery operation up to 18h depending on program used
  - <p>EUROLITE SB-14 Soft Bag

### Logistic

**Practical black soft bag, divided into 4 compartments, for 4 AKKU Flat Lights**

- With 2 Outside pockets
- With 4 compartments
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
- 2 carrying straps
- <p>EUROLITE Charger 4x Akku Flat Light Series

**Power supply with cable for simultaneous charging of 4 x AKKU Flat Light 1/3**

**Technical specifications:**

Weight: 7.51 kg

**EUROLITE AKKU Flat Light 1 sil**

|                         |                                                                                                                                        |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz<br>12.6V DC 2500 mA                                                                                             |
| Protection class:       | Protection class III                                                                                                                   |
| Power connection:       | Battery/battery pack<br>Mains input via coaxial power connector (M)<br>mounting version power supply cord with Euro<br>plug (provided) |
| Lamp type:              | LED lamp                                                                                                                               |
| LED type:               | 1 x 15 W SMD 9080 4in1 RGBW (homogenous<br>color mix)                                                                                  |
| DMX channels:           | 3; 4; 6; 8; 10                                                                                                                         |
| DMX input:              | 1 x 3-pin XLR (M) mounting version                                                                                                     |
| DMX output:             | 1 x 3-pin XLR (F) mounting version                                                                                                     |
| Cooling:                | Passive convection cooling                                                                                                             |
| Control:                | Master/slave function; stand-alone; IR remote<br>control; sound to light via microphone; QuickDMX                                      |
| Fixtures available for: | LED PC-Control 512; EASY SHOW 1; LED EASY<br>OPERATOR 4x4; LED EASY OPERATOR 4x6;<br>LED EASY OPERATOR DELUXE; Light Captain           |
| Projection:             | Flicker-free                                                                                                                           |
| Carrier frequency:      | 2.4 GHz                                                                                                                                |
| Beam angle:             | 8°                                                                                                                                     |
| Beam angle (1/2 peak):  | 8°                                                                                                                                     |
| Housing color:          | Silver                                                                                                                                 |
| Dimensions:             | Width: 16.8 cm<br>Depth: 13.8 cm<br>Height: 6.2 cm                                                                                     |
| Weight:                 | 1.67 kg                                                                                                                                |
| Noise classification:   | Class 0 (no noise at all)                                                                                                              |
| Battery:                | 1 x button cell 3.0 V CR2032 lithium manganese<br>built-in                                                                             |
| Battery pack type:      | 1 x lithium ion 11.1 V, 2600 mAh, 28.86 Wh                                                                                             |
| Battery pack:           | Battery operation up to 18h depending on<br>program used                                                                               |

---

Recharging time 4h

---

#### **EUROLITE SB-14 Soft Bag**

|                 |                                               |
|-----------------|-----------------------------------------------|
| Carrying strap: | 2 pc/pcs                                      |
| Material:       | Nylon                                         |
| Color:          | Black, water repellent                        |
| Dimensions:     | Width: 28 cm<br>Depth: 22 cm<br>Height: 18 cm |
| Weight:         | 0.34 kg                                       |

#### **EUROLITE Charger 4x Akku Flat Light Series**

|                   |                                                                                                |
|-------------------|------------------------------------------------------------------------------------------------|
| Power supply:     | 100-240 V AC, 50/60 Hz<br>12.6V DC 6000 mA                                                     |
| Power connection: | Mains input via C8 (M) "figure 8" mounting version power supply cord with Euro plug (provided) |
| Power output:     | 4 x coaxial power connector (F)                                                                |
| Weight:           | 0.49 kg                                                                                        |

#### **Scope of delivery:**

---

##### **4 x EUROLITE AKKU Flat Light 1 sil**

1 x remote control  
1 x device  
1 x user manual  
1 x external mains adapter

##### **1 x EUROLITE Charger 4x Akku Flat Light Series**

1 x charger  
1 x power cord  
1 x adapter cable