

EUROLITE Set LED KLS-170 Compact Light Set + M-4 Speaker-System Stand No.: 20000453

LED KLS-170 Compact Light Set including aluminum speaker stand

GTIN:



Features:

- Compact lightweight
 - Crossbar with integrated DMX control unit and stand sleeve
 - 31 integrated show programs
 - Can be operated in 3; 6; 16; 25 CH mode
 - The device is cooled by passive convection cooling
 - Control via stand-alone; DMX; wireless footswitch; IR remote control; sound to light via microphone; master/slave function
 - With a beam angle of 13°
 - With mounting bracket
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Party room; mobile use; mobile djs / entertainer; small rental
 - Silent operation
 - Application possibility: On stand
- spotlight**
- 3 LEDs 9 W SMD 8072 3in1 RGB (homogenous color mix)
 spots controlled separately
- bar**
- 4 LEDs 2 W high-power 2in1 CW/UV (homogenous color mix)
 LEDs controlled separately
- <p>OMNITRONIC M-4 Speaker-System Stand
- Aluminum speaker stand, height adjustable 140-345 cm, maximum load 18 kg**
- Durable aluminum version
 - Tube diameter: Ø 35 mm
 - Adjustable height

Logistic

Technical specifications:

Weight:	9.55 kg
---------	---------

EUROLITE LED KLS-170 Compact Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	90 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Lamp type:	LED lamp
DMX channels:	3; 6; 16; 25
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; wireless footswitch; IR remote control; sound to light via microphone; master/slave function
Fixtures available for:	EASY SHOW 1; Light´J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	13°
Beam angle (1/2 peak):	13°
Beam angle (1/10 peak):	25°
Housing color:	Black
Attachment system:	2x mounting bracket
Dimensions:	Width: 103 cm Depth: 55 cm Height: 24 cm
Weight:	6.25 kg
Noise classification:	Class 0 (no noise at all)
LED type:	3 x 9 W SMD 8072 3in1 RGB (homogenous color mix)
Battery:	1 x 9.0 V E block 6F22 zinc carbon included
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
LED type:	4 x 2 W high-power 2in1 CW/UV (homogenous color mix)
Flash rate:	0 - 30 Hz

OMNITRONIC M-4 Speaker-System Stand

Maximum carrying capacity:	18 kg
----------------------------	-------

Tube diameter sector:	38 - 35 mm
Height:	Maximum: 345 cm Minimum: 140 cm Adjustable in 10 steps with locking pin
Attachment system:	Ø 35mm
Type (general stands):	Speaker stand/manual
Material:	Aluminum
Color:	Black
Transport dimensions:	140 cm x 13.5 cm
Weight:	3.30 kg

Scope of delivery:

1 x EUROLITE LED KLS-170 Compact Light Set

1 x spotlight
 1 x user manual
 1 x power cord
 1 x bag
 1 x foot control
 1 x remote control
 2 x battery
 2 x mounting bracket
 2 x knurled screw
 2 x washer

1 x OMNITRONIC M-4 Speaker-System Stand

1 x user manual