

EUROLITE Set 4x AKKU Flat Light 3 sil + Case

4x flat spotlight with 3 x 8 W RGBW LED including PRO flightcase

Art. No.: 20000471

GTIN:



Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Elegant housing for indoor use
- Cordless, flexible and versatile
- Battery operation up to 16h depending on program used
- Integrated automatic charging of the battery and status indicator
- 3 LEDs 8 W SMD 9080 4in1 RGBW (homogenous color mix)
- Dimmer curves with adjustable response; color blend stepless; color change adjustable; colors preset; Dimmer electronic
- Strobe effect
- Can be operated in 3; 4; 6; 8; 10 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; QuickDMX; sound to light via microphone; IR remote control
- Flicker-free
- With a beam angle of 12°
- With mounting bracket
- Various versions available
- With a KENSINGTON LOCK theft protection
- For application areas such as: Small rental; wedding/gala/events
- Silent operation
- <p>ROADINGER Flightcase 4x AKKU Flat Light Series
- **Carrying case, PRO version**
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Rugged carrying handle
- 1 high-quality butterfly lock

Logistic

- Closes with a
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	10.63 kg
EUROLITE AKKU Flat Light 3 sil	
Power supply:	100-240 V AC, 50/60 Hz 12.6V DC 2500 mA
Pin configuration:	Inside + / outside -
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via coaxial power connector (M) mounting version power supply cord with Euro plug (provided)
Battery pack type:	1 x lithium ion 11.1 V, 5200 mAh, 57.72 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	3 x 8 W SMD 9080 4in1 RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 10
Cooling:	Passive convection cooling
Control:	Stand-alone; QuickDMX; sound to light via microphone; IR remote control
Fixtures available for:	Light J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle:	12°
Beam angle (1/2 peak):	12°
Beam angle (1/10 peak):	30°
Housing color:	Silver
Attachment system:	Mounting bracket
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 16.8 cm Depth: 13.8 cm Height: 6.2 cm
Weight:	1.62 kg
Noise classification:	Class 0 (no noise at all)

Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
----------	---

ROADINGER Flightcase 4x AKKU Flat Light Series

Aluminum profile frames:	25 mm
Carrying handle:	1 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	8 cm x 19 cm x 10 cm
Accessory compartment:	38 cm x 6.5 cm x 12 cm
Inside dimensions:	38 cm x 27 cm x 12 cm
Dimensions:	Width: 42 cm
	Depth: 31 cm
	Height: 20 cm
Weight:	4.15 kg

Scope of delivery:

- 1 x device
- 1 x user manual
- 1 x external mains adapter
- 1 x remote control
- 1 x declaration of conformity
- 1 x power cord