

EUROLITE Set LED SL-400 DMX + STV-200

Follow spot with 300 W warm white LED including follow spot stand PRO version

Art. No.: 20000479

GTIN:



Features:

- Manual control via control panel with buttons and faders
- 1 LED 300 W COB (chip-on-board) warm white (WW)
- Focus manual; iris stepless
- Dimmer electronic
- Strobe effect
- Color wheel with 5 dichroic filters plus open
half colors selectable
- Can be operated in 6 CH mode
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX
- Flicker-free
- With a beam angle of 7° - 17°
- Direct color temperature selection for 4 preset values
- Good color rendering index (CRI)
- With mounting bracket
- 4 digit 7-segment LED display
- Built with SEETRONIC connector
- Suitable for a range of use from 25 to 50 meters
- For application areas such as: Wedding/gala/events; stage; theater; rental
- Application possibility: Suspended; on stand
- <p>EUROLITE STV-200 Follow Spot Stand, Stainless Steel
- **PRO version with ball bearing head, maximum load 50 kg, maximum height 160 cm**
- Professional follow stand for mobile lighting systems
- Stand head lies on a ball-bearing
- Heavy-duty stainless steel version for extra stability and safety
- Easy handling
- Safety ring for height adjustment

Logistic

- Adjustable height

Technical specifications:

Weight:	18.65 kg
---------	----------

EUROLITE LED SL-400 DMX Search Light

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	440 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	1 x 300 W COB (chip-on-board) warm white (WW)
Flash rate:	0.8 - 16 Hz
Equipment:	Focus manual; iris stepless
Color generation:	Color wheel with 5 dichroic filters plus open Half colors selectable
DMX channels:	6
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX
Fixtures available for:	LED PC-Control 512; Light Captain
Projection:	Flicker-free
PWM frequency:	26600 Hz
Beam angle:	7° - 17°
Beam angle (1/2 peak):	7 - 17°
Beam angle (1/10 peak):	7 - 17°
Color temperature:	3500K
Color rendering index (CRI):	80 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Use of brands:	Built with SEETRONIC connector
Range of use:	25m - 50m
Dimensions:	Length: 77 cm Width: 27 cm Height: 29 cm
Weight:	12.35 kg
Noise classification:	Class 2 (slight noise)

EUROLITE STV-200 Follow Spot Stand, Stainless Steel

Maximum carrying capacity:	50 kg
Height:	Maximum: 160 cm Minimum: 110 cm
Attachment system:	M12 thread
Type (general stands):	Light stand/manual
Material:	Aluminum; stainless steel
Color:	Silver
Weight:	6.30 kg

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x XLR cable
- 1 x mounting bracket
- 1 x hex key