

EUROLITE Set LED SL-350 DMX + Case

Follow spot with cold white 300 W LED including PRO flightcase

Art. No.: 20000483

GTIN: 4026397642711



List price: 2081.31 €

incl. 19% VAT.

Features:

- Manual control via control panel with buttons and faders
 - 1 LED 300 W COB (chip-on-board) cold white (CW)
 - Focus manual; iris stepless
 - Dimmer electronic
 - Strobe effect
 - Color wheel with 5 dichroic filters plus open
 - Can be operated in 6 CH mode
 - The device is cooled by cooling fan
 - Control via stand-alone; DMX
 - With a beam angle of 10°
 - Direct color temperature selection for 3 preset values
 - With mounting bracket
 - 4 digit 7-segment LED display
 - Suitable for a range of use from 10 to 30 meters
 - For application areas such as: Stage; wedding/gala/events; theater; rental
 - Application possibility: Suspended; on stand
 - <p>ROADINGER Flightcase SL-160/SL-350
- Trunk case, PRO version**
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
 - Interior with foam padding
 - Aluminum profile frames 25mm with rounded edges
 - 2 hinged, chromium plated case handles
 - 2 chrome tip-over locks
 - 2 high-quality butterfly locks
 - Closes with a
 - Branded hardware

Logistic

EAN / GTIN: 4026397642711

Weight: 21,20 kg

Length: 1.30 m

Width: 0.50 m

Height: 0.30 m

Bulky product

- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	19.75 kg
---------	----------

EUROLITE LED SL-350 DMX Search Light

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	440 W
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 5 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 300 W COB (chip-on-board) cold white (CW)
Flash rate:	0 - 20 Hz
Equipment:	Focus manual; iris stepless
Color generation:	Color wheel with 5 dichroic filters plus open
DMX channels:	6
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX
Fixtures available for:	Light´ J; LED PC-Control 512; Light Captain
Beam angle:	10°
Beam angle (1/2 peak):	10°
Housing color:	Black matte
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum casting; metal
Range of use:	- 30m
Dimensions:	Length: 60 cm Width: 27.5 cm Height: 30 cm
Weight:	10.55 kg
Noise classification:	Class 2 (slight noise)
Cable construction:	3 x 1.5 mm² H05VV-F
Cable length:	Approx. 1.4 m
Cable length:	Approx. 2 m
Diameter mounting holes:	3 x Ø13mm; 2 x Ø15mm
Material:	Metal, 4 mm
Dimensions:	Width: 6 cm

ROADINGER Flightcase SL-160/SL-350

Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm; plywood multi-layer glued
Color:	Dark brown, laminated
Device compartment:	61 cm x 19.5 cm x 25 cm
Inside dimensions:	68 cm x 34 cm x 29 cm
Dimensions:	Width: 72 cm
	Depth: 38 cm
	Height: 34.5 cm
Weight:	9.20 kg

Scope of delivery:

1 x spotlight
1 x user manual
1 x power cord
1 x XLR cable
1 x mounting bracket
1 x hex key