



The article is no longer in our assortment.

Features:

Logistic

EUROLITE TMH XB-130 Moving-Head-Beam

Bright, extremely narrow beam with Osram Sirius HRI 132 W lamp

- 11 or 14 DMX channels selectable
- Very narrow beam angle of 1°
- Effect wheel with rotating 8-facet prism
- The prism rotates in both directions and at different speeds
- Motorized focus
- Strobe effect with adjustable speed
- Random strobe effect
- Frost filter
- Dimmer
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- Switch-mode power supply for operation between 100 and 240 Volts
- Control board with LED display for adjusting the DMX-starting address, PAN/TILT reverse, reset, lamp on/off
- PAN-angle switchable between 630° and 540°
- DMX-controlled operation or stand-alone operation with master/slave function
- Software upload by optional accessory via DMX link
- Sound-controlled via built-in microphone
- With Osram Sirius HRI 132 W lamp

- Ready for connection via included IEC power cord with safety power plug
- Feed-through output allows to power up to 8 devices
- DMX-control via any standard DMX-controller
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with static gobos; prism 8-fold; frost filter; focus motor-driven
- Beam effect
- Color wheel with 14 dichroic filters plus open
rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 17 gobos and open
shake effect
- Can be operated in 11; 14 CH mode
- The device is cooled by temperature-controlled fan
- Control via stand-alone; sound to light via microphone
- With a beam angle of 1°
- OSRAM bulb included

ROADINGER Flightcase 4x PLB-130/DMH-80/TMH XB-130

Trunk case with castors

- With 4 device compartments
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

EUROLITE TMH XB-130 Moving-Head-Beam

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	170 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	Discharge lamp
Max. TILT movement:	270° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540°, 630° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 20 Hz
Equipment:	Gobo wheel with static gobos; prism 8-fold; frost filter; focus motor-driven
Color generation:	Color wheel with 14 dichroic filters plus open Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 17 gobos and open Shake effect

DMX channels:	11; 14
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; sound to light via microphone
Fixtures available for:	LED PC-Control 512; Light Captain; Light´J
Beam angle:	1°
Beam angle (1/2 peak):	1°
Housing color:	Black
Use of brands:	OSRAM bulb included
Dimensions:	Width: 29 cm Depth: 26 cm Height: 40 cm
Weight:	10.65 kg

ROADINGER Flightcase 4x PLB-130/DMH-80/TMH XB-130

Maximum load:	100 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Accessory compartment:	10 cm x 45 cm x 38.5 cm
Inside dimensions:	77 cm x 45 cm x 40.5 cm
Device compartment:	31.5 cm x 21.5 cm x 38.5 cm
Dimensions:	Width: 81 cm Depth: 50 cm Height: 43 cm
Weight:	22.60 kg

Scope of delivery:

1 x omega bracket