

EUROLITE Set 2x LED Umbrella 140 + DMX LED Color Chief + 2x BS-2 EU stand.: 20000494

2x LED Umbrella with DMX lighting desk, 2x high steel speaker stand and adapter

GTIN:



Features:

- DMX-controllable lighting effect umbrella with 114 SMD RGB LEDs, distributed in 7 segments
- Segments can be controlled individually via DMX
- 6 segments make the surface of the umbrella shine, one segment in the middle shines directly at the audience
- Perfect as stage background and eye-catcher for decorative purposes in shops, display windows, fair stands, hotels, bars and clubs
- Can be mounted to a lighting stand or trussing - the umbrella's angle can be adjusted
- Easy transport (can be folded), setup and installation
- Covers a large area with a diameter of 140 cm
- Built-in auto and music show programs
- Supports QuickDMX - the wireless DMX-system from Eurolite
- Built-in phantom-powered USB port for QuickDMX receivers (accessories)
- Stepless RGB color mixture, dimmer and strobe effect
- Addressing via control panel with 4-digit LED display
- Appropriate control unit included in the delivery
- Power connection via P-Con jack and included power cable with safety plug
- 114 LEDs SMD 5050 3in1 RGB (homogenous color mix)
- Can be operated in 6; 24 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- <p>EUROLITE DMX LED Color Chief Controller
- **DMX lighting desk with innovative control concept for LED spotlights**
- Easy control of LED spotlights with up to 6 colors, light bars as well as simple lighting effects

Logistic

- For 8 devices or device groups, each with up to 4 segments
- Quick and easy programming
- Additional fixtures can be configured manually
- 8 color effects directly selectable
- 3 additional channels available per fixture (e.g. for rotations)
- Color wheel selection and simulation
- 24 memory spaces for scenes and chases
- Several chases and scenes can be run simultaneously
- USB port for storing program data
- Sound control via audio signal or TAP button
- Master dimming, fade time and run time easily adjustable
- Can transmit up to 240 DMX channels
- (19") 48.3 cm rack installation 3 U
- Programmable 24 scenes/chases distributed over 1 page/s
- Control via DMX; sound to light via RCA (F) mounting version; sound to light via microphone
- Firmware can be updated
- Desktop console housing
- For application areas such as: Clubs/dancing school; party room; Trade fair and shop fitting; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- <p>OMNITRONIC BS-2 EU Loudspeakerstand
- High steel speaker stand, height adjustable 117-205 cm, maximum load 50 kg**
- Height adjustable, with locking pin
- Tube diameter: Ø 35 mm
- Adjustable height
- Made in Europe
- <p>EUROLITE SPA-10S Adapter
- For 35 mm tube with screw thread and M10 wing bolt, max. load WLL 100 kg**
- Adapter for installing a spot, speaker system etc. on a stand
- M10 wing bolt
- M10 thread

Technical specifications:

Weight:	18.96 kg
---------	----------

EUROLITE LED Umbrella 140

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	114 x SMD 5050 3in1 RGB (homogenous color mix)
DMX channels:	6; 24
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light´J; LED PC-Control 512; Light Captain

Projection:	Flicker-free
Dimensions:	Diameter: Ø 140 cm
Weight:	3.07 kg

EUROLITE DMX LED Color Chief Controller

Power supply:	100-240 V AC, 50/60 Hz 9V DC 800 mA
Power consumption:	7.2 W
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Programmable 24 scenes/chases distributed over 1 page/s
DMX channels:	Output 240
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; sound to light via RCA (F) mounting version; sound to light via microphone
Housing color:	Black
Available storage media:	USB devices (FAT 32)
USB port:	Type A
Color:	Black
PC connect:	, firmware can be updated
Housing design:	(19") 48.3 cm rack installation 3 U Desktop console housing
Dimensions:	Width: 48.3 cm Depth: 13.35 cm Height: 8.5 cm
Weight:	2.25 kg
Noise classification:	Class 0 (no noise at all)

OMNITRONIC BS-2 EU Loudspeakerstand

Maximum carrying capacity:	50 kg
Height:	Maximum: 205 cm Minimum: 117 cm
Attachment system:	Ø 35mm
Type (general stands):	Speaker stand/manual
Material:	Steel
Color:	Black
Transport dimensions:	110 cm x 17 cm x 14 cm
Weight:	4.90 kg

EUROLITE SPA-10S Adapter

Maximum load BGV C1 (8-fold):	50 kg
-------------------------------	-------

Maximum load WLL (4-fold):	100 kg
Attachment system:	Ø 35mm
Type (general stands):	Accessory
Material:	Steel, powder-coated
Plate:	1.3 cm Ø 6 cm
Thread:	M10 thread x 25 mm
Dimensions:	Height: 13 cm Diameter: Ø 6 cm
Weight:	0.38 kg

Scope of delivery:

2 x EUROLITE LED Umbrella 140

1 x omega bracket
1 x device
1 x user manual
1 x power cord
1 x multipin cable
1 x umbrella

1 x EUROLITE DMX LED Color Chief Controller

1 x controller
1 x user manual
1 x external mains adapter

2 x OMNITRONIC BS-2 EU Loudspeakerstand

1 x stand

2 x EUROLITE SPA-10S Adapter

1 x adapter
1 x user manual