

## OMNITRONIC PA Set AZX active L

Art. No.: 20000529

2x AZX-118A PA Subwoofer active 400W, 2x AZX-215A 2-way Top active 350 W including 2x distance tube

GTIN: 4026397651300



**List price: 2140.81 €**

incl. 19% VAT.

### Features:

- 46 cm (18") bass speaker with 76 mm voice coil
- Class D amplifier with 400 W
- XLR inputs and parallel outputs L/R
- XLR output L/R with high-pass filter
- Adjustable crossover frequency 80-200 Hz
- Black metal grille with acoustic foam
- Rugged carrying handle
- For application areas such as: Clubs/dancing school; installation; mobile use; mobile djs / entertainer; rental
- <p>OMNITRONIC AZX-215A 2-way top active 350W
- **Active speaker with 15" woofer, 1.75" driver, 300 W RMS LF, 50 W RMS HF**
- 2-way bass-reflex enclosure with 38 cm woofer and 4.5 cm titanium driver
- Master control with 2-band EQ
- HF adjustment -4 dB, -2 dB, 0 dB
- Dual flange
- With rigging points
- Black metal grille with acoustic foam
- Rugged carrying handle
- Application possibility: Standing; suspended; monitoring; on stand
- For application areas such as: Clubs/dancing school; installation; mobile use; mobile djs / entertainer; rental
- <p>OMNITRONIC Distance Tube Subwoofer/Satellite M20
- **Variable distance tube, M20 thread, height adjustable 75-130 cm, max. load 30 kg**
- Connecting tube for satellite systems
- Locking screw and bolt
- Powder-coated steel version

### Logistic

EAN / GTIN: 4026397651300  
Weight: 72,00 kg  
Length: 1.20 m  
Width: 0.80 m  
Height: 1.20 m

- Adjustable height
- M20 thread

## Technical specifications:

|         |           |
|---------|-----------|
| Weight: | 118.10 kg |
|---------|-----------|

### OMNITRONIC AZX-118A PA Subwoofer active 400W

|                       |                                                                                                        |
|-----------------------|--------------------------------------------------------------------------------------------------------|
| Power supply:         | 230 V AC, 50 Hz                                                                                        |
| Power consumption:    | 650 W                                                                                                  |
| Protection class:     | Protection class I                                                                                     |
| Power connection:     | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)       |
| Fuse:                 | 5 x 20 mm, T 3.15 A fuse replaceable                                                                   |
| Power:                | Rated: 400W RMS                                                                                        |
| Frequency range:      | 40 - 250 Hz                                                                                            |
| Sensitivity:          | 95 dB (1W/1m)                                                                                          |
| Attachment system:    | Flange: M20 thread                                                                                     |
| Circuitry:            | Class D                                                                                                |
| Control elements:     | Phase reversal switch                                                                                  |
| Controls:             | Limiter                                                                                                |
| Status LED:           | Limit, power, signal                                                                                   |
| Connections:          | Input: line via 2 x 3-pin XLR<br>Output: line via 2 x 3-pin XLR<br>Output: high-pass via 2 x 3-pin XLR |
| Crossover frequency:  | 80-200 Hz                                                                                              |
| Speaker:              | 1 x woofer 18"<br>Basket material: steel<br>Voice coil lows 2.5"                                       |
| Type of speaker:      | Subwoofer                                                                                              |
| Type of construction: | Vented                                                                                                 |
| Carrying handle:      | 1 pc/pcs                                                                                               |
| Material:             | MDF (medium density fiberboard), 15 mm                                                                 |
| Color:                | Black, textured coating, painted                                                                       |
| Dimensions:           | Width: 61.3 cm<br>Depth: 61.3 cm<br>Height: 54 cm                                                      |
| Weight:               | 32.70 kg                                                                                               |

### OMNITRONIC AZX-215A 2-way top active 350W

|                    |                 |
|--------------------|-----------------|
| Power supply:      | 230 V AC, 50 Hz |
| Power consumption: | 650 W           |

|                    |                                                                                                              |
|--------------------|--------------------------------------------------------------------------------------------------------------|
| Power connection:  | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)             |
| Power:             | Rated: 300W RMS LF<br>Rated: 50W RMS HF                                                                      |
| Frequency range:   | 50 - 20000 Hz                                                                                                |
| Sensitivity:       | 95 dB (1W/1m)                                                                                                |
| Attachment system: | Dual flange: Ø 35mm (0° / 5°)                                                                                |
| Flying points:     | 7 x M10 thread                                                                                               |
| Circuitry:         | Class D Biamp                                                                                                |
| Controls:          | Limiter                                                                                                      |
| Status LED:        | Limit, power, signal                                                                                         |
| Connections:       | Input: 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)<br>Output: line via 1 x 3-pin XLR |
| Input channels:    | 1 x mono with mic-line switch via Combination socket (XLR/jack), channel control via rotary dial             |
| Equalizer:         | Master: 1 x 2-band tone control                                                                              |
| Speaker:           | Woofer 15" with ferrit magnet<br>Voice coil lows 3"<br>Voice coil compression tweeter highs 1.75"            |
| Type of speaker:   | Compact cabinet speaker                                                                                      |
| Carrying handle:   | 1 pc/pcs                                                                                                     |
| Material:          | MDF (medium density fiberboard), 15 mm                                                                       |
| Color:             | Black, textured coating, painted                                                                             |
| Dimensions:        | Width: 43 cm<br>Depth: 43 cm<br>Height: 73 cm                                                                |
| Weight:            | 25.45 kg                                                                                                     |

#### OMNITRONIC Distance Tube Subwoofer/Satellite M20

|                            |                                   |
|----------------------------|-----------------------------------|
| Maximum carrying capacity: | 30 kg                             |
| Tube diameter sector:      | 41 - 35 mm                        |
| Height:                    | Maximum: 130 cm<br>Minimum: 75 cm |
| Attachment system:         | Ø 35mm                            |
| Type (general stands):     | Distance tube                     |
| Color:                     | Black                             |
| Thread:                    | M20 thread                        |
| Weight:                    | 0.90 kg                           |

#### Scope of delivery:

#### 2 x OMNITRONIC AZX-118A PA Subwoofer active 400W

1 x bass  
1 x user manual  
1 x power cord

**2 x OMNITRONIC AZX-215A 2-way top active 350W**

1 x compact cabinet speaker  
1 x user manual  
1 x power cord

**2 x OMNITRONIC Distance Tube Subwoofer/Satellite M20**

1 x distance tube  
1 x user manual