

## OMNITRONIC Set BOB-10A bk + 4x BOB-4 bk

BOB-10A Subwoofer active including 4 x 4" satellite speakers BOB-4

Art. No.: 20000533

GTIN: 4026397651355



**List price: 760.41 €**

incl. 19% VAT.

### Features:

- 10" bassreflex subwoofer with DSP and 900 watts RMS power
- Flexibly extendable with BOB-4 satellites for 2.1, 4.1 and 8.1 configurations
- DSP-controlled class D amplifier (300 W + 2 x 300 W)
- Signal inputs via combo jacks (XLR/6.3 mm jack) and RCA
- Separate volume control for subwoofer and satellites
- Stereo/mono selection
- Digital signal processor
- DSP presets: FLAT; DJ; LIVE; SPEECH
- The device is cooled by passive convection cooling
- Control via Bluetooth
- Bluetooth: operating range up to 10m in buildings
- Black metal grille with acoustic foam
- 4 Rugged carrying handles
- For application areas such as: Mobile djs / entertainer; Trade fair and shop fitting; installation; home entertainment; restaurants, bars and hotels; product presentations and lectures
- <p>OMNITRONIC BOB-4 Top 16 Ohm black 2x  
**2 x 4" satellite speakers with bracket for the BOB series**
- 16-ohm speaker pair with 4" full-range speaker
- For use with BOB-10A subwoofers for 2.1, 4.1 and 8.1 configurations
- Optional stand adaptor required for stand mounting
- Extension U-bracket and cable available for connecting 2 satellite speakers
- With mounting bracket
- Black metal grille with acoustic foam
- 2 pieces per set
- For application areas such as: Mobile djs / entertainer; Trade fair and shop fitting; installation; home entertainment; restaurants, bars and hotels; product presentations and lectures

### Logistic

EAN / GTIN: 4026397651355

Weight: 26,90 kg

Length: 0.52 m

Width: 0.57 m

Height: 0.50 m

## Technical specifications:

|         |          |
|---------|----------|
| Weight: | 24.95 kg |
|---------|----------|

### OMNITRONIC BOB-10A Subwoofer active black

|                        |                                                                                                                                                                              |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:          | 230 V AC, 50 Hz                                                                                                                                                              |
| Power consumption:     | 1060 W                                                                                                                                                                       |
| Protection class:      | Protection class I                                                                                                                                                           |
| Power connection:      | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)                                                                             |
| Fuse:                  | 5 x 20 mm, T 3.15 A fuse replaceable                                                                                                                                         |
| Power:                 | Rated: 1x 300W RMS LF<br>Rated: 2x 300W RMS HF                                                                                                                               |
| Frequency range:       | 45 - 250 Hz                                                                                                                                                                  |
| Sensitivity:           | 100 dB                                                                                                                                                                       |
| Max. SPL:              | 125 dB                                                                                                                                                                       |
| DSP:                   | Digital signal processor                                                                                                                                                     |
| DSP presets:           | FLAT; DJ; LIVE; SPEECH                                                                                                                                                       |
| Cooling:               | Passive convection cooling                                                                                                                                                   |
| Control:               | Bluetooth                                                                                                                                                                    |
| Bluetooth device name: | Omnitronic BOB                                                                                                                                                               |
| Range:                 | Bluetooth: range up to 10m in buildings                                                                                                                                      |
| Attachment system:     | 2x M20 thread                                                                                                                                                                |
| Circuitry:             | Class D                                                                                                                                                                      |
| Control elements:      | Phase reversal switch                                                                                                                                                        |
| Controls:              | Softstart; short-circuit; limiter; Overvoltage; overheat; limiter                                                                                                            |
| Status LED:            | Signal, power, limit, fault, DSP presets                                                                                                                                     |
| Connections:           | Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)<br>Output: speaker via 2 x speaker built-in socket (F)<br>Output: line via 2 x 3-pin XLR |
| Input channels:        | 1 x stereo via combination socket or RCA or Bluetooth, channel control via rotary dial                                                                                       |
| Speaker:               | 1 x woofer 10"<br>Basket material: steel<br>Conematerial: cardboard/paper<br>Voice coil lows 2"                                                                              |
| Type of speaker:       | Subwoofer                                                                                                                                                                    |
| Type of construction:  | Vented                                                                                                                                                                       |
| Carrying handle:       | 4 pc/pcs                                                                                                                                                                     |
| Material:              | MDF (medium density fiberboard), 15 mm                                                                                                                                       |

|               |                                               |
|---------------|-----------------------------------------------|
| Color:        | Black, textured coating                       |
| Dimensions:   | Width: 30 cm<br>Depth: 47 cm<br>Height: 43 cm |
| Weight:       | 16.95 kg                                      |
| Cable length: | 3 m                                           |

#### OMNITRONIC BOB-4 Top 16 Ohm black 2x

|                    |                                                                                                                                            |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Power:             | Program: 150W<br>Rated: 75W RMS                                                                                                            |
| Frequency range:   | 150 - 16000 Hz                                                                                                                             |
| Sensitivity:       | 90 dB (1W/1m)                                                                                                                              |
| Max. SPL:          | 109 dB                                                                                                                                     |
| Dispersion angle:  | 120° x 120°                                                                                                                                |
| Impedance:         | 16 ohms                                                                                                                                    |
| Attachment system: | Mounting bracket                                                                                                                           |
| Connections:       | Input: speaker via 1 x screw plug-in terminal<br>Input: speaker via 1 x speaker built-in socket (F)                                        |
| Speaker:           | 1 x compression tweeter highs 4"<br>Basket material: steel<br>Conematerial: cardboard/paper<br>1 x voice coil compression tweeter highs 1" |
| Material:          | ABS Acrylonitrile butadiene styrene                                                                                                        |
| Color:             | Black, textured coating, painted                                                                                                           |
| Dimensions:        | Width: 15 cm<br>Depth: 16 cm<br>Height: 15.8 cm                                                                                            |
| Weight:            | 4.00 kg                                                                                                                                    |

#### Scope of delivery:

##### 1 x OMNITRONIC BOB-10A Subwoofer active black

1 x bass  
1 x user manual  
1 x power cord  
2 x speaker cable  
4 x foot  
4 x screw  
1 x declaration of conformity

##### 2 x OMNITRONIC BOB-4 Top 16 Ohm black 2x

2 x top  
4 x knurled screw  
2 x mounting bracket  
2 x plug (male)