

## EUROLITE Set 4x AKKU IP UP-4 QCL Spot QuickDMX + Case with charging function 0546

4x weather-proof Uplight with 4 x 10 W 4in1 LED including PRO flightcase with charging function GTIN:



### Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Additional frost filter provides a wide, soft and homogeneous light
- Cordless, flexible and versatile
- Battery operation up to 16h depending on program used
- Integrated automatic charging of the battery and status indicator
- 4 LEDs 10 W SMD 5050 4in1 RGBW (homogenous color mix)
- Dimmer speed (step response) adjustable; Dimmer electronic; color blend stepless; color change adjustable; colors preset
- Can be operated in 3; 4; 6; 8; 10 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX; sound to light via microphone; IR remote control; master/slave function
- Flicker-free
- With a beam angle of 7°
- With bracket for floor use
- LCD display
- Suitable for outdoor use IP65
- With a KENSINGTON LOCK theft protection
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Silent operation
- Application possibility: Standing
- <p>ROADINGER Flightcase 4x AKKU IP UP-4 QuickDMX with charging function
- Trunk case with castors**
- With accessory compartment
- With 4 device compartments

### Logistic

- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- Closes with a
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover

## Technical specifications:

|         |          |
|---------|----------|
| Weight: | 33.01 kg |
|---------|----------|

### EUROLITE AKKU IP UP-4 QCL Spot QuickDMX

|                         |                                                                                                                                                    |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                                             |
| IP classification:      | IP65                                                                                                                                               |
| Protection class:       | Protection class I                                                                                                                                 |
| Power connection:       | Battery/battery pack<br>Mains input via IP P-Con (Power in) yellow mounting version power supply cord with safety plug (provided)                  |
| Cable length:           | Approx. 1.2 m                                                                                                                                      |
| Battery pack type:      | 1 x lithium ion 14.8 V, 7800 mAh, 115.44 Wh                                                                                                        |
| Battery pack:           | Battery operation up to 16h depending on program used<br>Recharging time 3h                                                                        |
| Lamp type:              | LED lamp                                                                                                                                           |
| LED type:               | 4 x 10 W SMD 5050 4in1 RGBW (homogenous color mix)                                                                                                 |
| DMX channels:           | 3; 4; 6; 8; 10                                                                                                                                     |
| DMX input:              | 1 x 3-pin XLR (M) mounting version IP                                                                                                              |
| DMX output:             | 1 x 3-pin XLR (F) mounting version IP                                                                                                              |
| Cooling:                | Passive convection cooling                                                                                                                         |
| Control:                | Stand-alone; DMX; QuickDMX; sound to light via microphone; IR remote control; master/slave function                                                |
| Fixtures available for: | Light´ J; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Projection:             | Flicker-free                                                                                                                                       |
| Carrier frequency:      | 2.4 GHz                                                                                                                                            |
| Beam angle:             | 7°                                                                                                                                                 |
| Beam angle (1/2 peak):  | 7°                                                                                                                                                 |
| Beam angle (1/10 peak): | 20°                                                                                                                                                |
| Housing color:          | Black                                                                                                                                              |
| Attachment system:      | Bracket for floor use                                                                                                                              |

|                       |                                                         |
|-----------------------|---------------------------------------------------------|
| Display type:         | LCD display                                             |
| Theft protection:     | KENSINGTON LOCK                                         |
| Dimensions:           | Width: 15 cm<br>Depth: 18 cm<br>Height: 19.8 cm         |
| Weight:               | 4.44 kg                                                 |
| Noise classification: | Class 0 (no noise at all)                               |
| Battery:              | 1 x button cell 3.0 V CR2032 lithium manganese built-in |

#### **ROADINGER Flightcase 4x AKKU IP UP-4 QuickDMX with charging function**

|                          |                                                                                             |
|--------------------------|---------------------------------------------------------------------------------------------|
| Power supply:            | 100-240 V AC, 50/60 Hz                                                                      |
| Power consumption:       | Max. 1150 W                                                                                 |
| Power connection:        | Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided) |
| Fuse:                    | 5 x 20 mm, F 5 A fuse replaceable                                                           |
| Aluminum profile frames: | 25 mm                                                                                       |
| Case handle:             | 4 pc/pcs                                                                                    |
| Stop hinge:              | 2 pc/pcs                                                                                    |
| Lock:                    | Butterfly lock: 2 pc/pcs with shut-off function                                             |
| Transport aid:           | 4 x castors with 2 locking brakes<br>4 x built-in stacking trays in the cover               |
| Material:                | Plywood multi-layer glued, 9 mm                                                             |
| Color:                   | Black, laminated                                                                            |
| Device compartment:      | 18 cm x 15.5 cm x 14 cm                                                                     |
| Accessory compartment:   | 7 cm x 43 cm x 14 cm                                                                        |
| Inside dimensions:       | 56 cm x 43 cm x 20 cm                                                                       |
| Dimensions:              | Width: 60 cm<br>Depth: 47.5 cm<br>Height: 41 cm                                             |
| Weight:                  | 15.25 kg                                                                                    |
| Cable construction:      | 3 x 1.5 mm² H07RN-F                                                                         |
| Cable length:            | 1.2 m detachable                                                                            |

#### **Scope of delivery:**

##### **4 x EUROLITE AKKU IP UP-4 QCL Spot QuickDMX**

1 x spotlight  
 1 x user manual  
 1 x power cord  
 1 x frost filter  
 1 x remote control  
 1 x battery  
 2 x knurled screw  
 1 x mounting bracket  
 2 x screw  
 1 x declaration of conformity

##### **1 x ROADINGER Flightcase 4x AKKU IP UP-4 QuickDMX with charging function**

1 x case  
 1 x power cord

4 x castors  
16 x screw  
1 x key  
1 x user manual