



The article is no longer in our assortment.

Features:

- Flexible LED strip for decorative lighting
- High-grade components and a solid construction ensure excellent color rendering
- Can be cut into segments of variable size
- Self-adhesive rear side
- Supplied on a plastic reel
- Power cable, straight and flexible plug connectors available as accessories
- 300 LEDs SMD 3528 warm white (WW)
- Control via accessory
- Very high color rendering index (CRI)
- For application areas such as: Trade fair and shop fitting; clubs/dancing school; installation; restaurants, bars and hotels
- Silent operation
- <p>EUROLITE LED Strip Receiver Zone Single Color
- **Wireless receiver for controlling single-colored LED strips 12-24 V**
- For dimming single-colored LED strips 12-24 V
- 2 channels
- <p>EUROLITE LED Strip Remote Control Zone Single Color
- **Wireless remote control for single-colored LED strips 12-24 V**
- Controls 4 zones
- Multiple remote controls possible in one zone
- Powered by a battery/battery pack
- Dimmer electronic
- Operating range up to 30m
- <p>EUROLITE Electr. LED Transformer, 12V, 4A
- **Stabilized LED power supply unit DC 12 V, 4 A**
- Especially for LED installations

Logistic

- Input voltage AC 100-240 V

Technical specifications:

Weight:	0.66 kg
---------	---------

EUROLITE LED Strip 300 5m 3528 2700K 12V

Power supply:	12V DC
Power consumption:	18 W
Protection class:	Protection class III
Power connection:	Fixed supply cord with open wires
Lamp type:	LED lamp
LED type:	300 x SMD 3528 warm white (WW)
Control:	Accessory
Standing/fixation:	Self adhesive
Color temperature:	2700K
Color rendering index (CRI):	93 Ra
Lamps/meter:	60 pc/pcs
Power/meter:	3.6 W
Lamps/tube:	300 pc/pcs
Lamp distance:	16 mm
Cutting mark:	5 cm
Luminous flux (Lumen) per meter:	360 lm/m
Housing color:	White
Dimensions:	Length: 500 cm Width: 0.8 cm Height: 0.2 cm
Weight:	0.09 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	G

EUROLITE LED Strip Receiver Zone Single Color

Power supply:	12/24V DC
Power consumption:	Max. 192 W 12 V DC Max. 384 W 24 V DC 96 W 12 V DC per channel 192 W 24 V DC per channel
Output current:	Max. 2 x 8 A per channel
Power connection:	Via screw terminal
Power output:	Screw terminal
Carrier frequency:	2.4 GHz
Dimensions:	Length: 11.5 cm

	Width: 4.5 cm
	Height: 3.2 cm
Weight:	0.08 kg

EUROLITE LED Strip Remote Control Zone Single Color

Battery:	2 x 1.5 V AAA Micro LR03 alkaline manganese included
Range:	Range up to 30m
Carrier frequency:	2.4 GHz
Dimensions:	Length: 14.7 cm Width: 4 cm Height: 2.8 cm
Weight:	0.09 kg

EUROLITE Electr. LED Transformer, 12V, 4A

Power supply:	100-240 V AC, 50/60 Hz
Protection class:	Protection class II
Power connection:	Mains input via screw terminal
Power output:	Screw terminal
Housing color:	White matte
Controls:	Overload; short-circuit; overheat
Output:	12V DC, stabilized; 4 A;
Material:	Plastic
Dimensions:	Length: 18 cm Width: 4 cm Height: 2.5 cm
Weight:	0.16 kg

EUROLITE LED Strip Power Contact 2-Pin 8mm

Material:	Plastic
Color:	Multicolor
Dimensions:	Length: 16 cm Width: 1.30 cm Height: 0.70 cm
Weight:	0.01 kg

Scope of delivery:

1 x EUROLITE LED Strip 300 5m 3528 2700K 12V

1 x illuminant
1 x user manual

2 x EUROLITE Electr. LED Transformer, 12V, 4A

1 x external mains adapter