



Features:

Logistic

EUROLITE LED PAR-64 COB 3000K 100W Zoom bk

PAR spot with warm white 100 W COB LED and manual zoom

- Light performance comparable to a traditional 1000 W halogen spot light
- Homogeneous light distribution
- Very high color rendering index (CRI)
- Flicker-free
- 1 LED 100 W COB (chip-on-board) warm white (WW)
- Control via DMX
- Dimmer speed (step response) adjustable; Gamma correction adjustable; pulse-width modulation variable
- Strobe effect
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; video and photography
- Application possibility: Suspended; on stand
- Can be operated in 1; 2; 3 CH mode
- With a beam angle of 11° - 48°

ROADINGER Flightcase EP-64 4x PAR-64 Spot long

Trunk case

- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, black, laminated
- Interior with felt cover
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Closes with a
- Plastic feet
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	26.70 kg
---------	----------

EUROLITE LED PAR-64 COB 3000K 100W Zoom bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) warm white (WW)
Flash rate:	0 - 25 Hz
DMX channels:	1; 2; 3
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX
Fixtures available for:	Light´J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	11° - 48°
Beam angle (1/2 peak):	11 - 35°
Beam angle (1/10 peak):	15 - 48°
Color temperature:	3000K
Color rendering index (CRI):	91 Ra
Illuminance in Lux (lx):	Narrow warm white (WW) 3m: 15535 lx, 6m: 3666 lx Wide warm white (WW) 3m: 2387 lx, 6m: 654 lx
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum; metal
Dimensions:	Width: 26 cm

	Depth: 43.5 cm Height: 37.5 cm
Weight:	3.55 kg
Noise classification:	Class 2 (slight noise)
Cable construction:	3 x 1.0 mm ² H05VV-F
Cable length:	Approx. 1.5 m
Shape:	Octagonal
Material:	Aluminum, 0.5 mm
Dimensions:	Width: 24.8 cm Height: 24.8 cm Diameter: Ø 19.8 cm
Cable length:	Approx. 1.8 m
Diameter mounting holes:	1 x Ø10mm; 2 x Ø8mm
Material:	Aluminum, 4 mm

ROADINGER Flightcase EP-64 4x PAR-64 Spot long

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Transport aid:	Plastic feet
Material:	Birch multiplex, 7 mm
Color:	Black, laminated
Compartment dimensions:	23 cm x 23 cm x 41.5 cm
Inside dimensions:	46 cm x 46 cm x 41.5 cm
Dimensions:	Width: 52 cm Depth: 52 cm Height: 53 cm
Weight:	12.50 kg

Scope of delivery:

1 x spotlight
 1 x power cord
 1 x filter frame
 1 x XLR cable
 1 x mounting bracket
 2 x knurled screw
 2 x washer
 1 x user manual