

EUROLITE Set 2x LED IP PAR 14x8W QCL + Case with wheels

2x weather-proof spotlight with RGBW color mixing, frost filters and PRO flightcase with wheels

Art. No.: 20000580

GTIN:



Features:

- 14 LEDs 8 W high-power 4in1 RGBW (homogenous color mix)
- Frost filter
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 18 preset colors
- Can be operated in 2; 3; 4; 8 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control
- Flicker-free
- With a beam angle of 15°
- With double bracket
- Monochrome LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- For application areas such as: Architecture; stage; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand
- <p>ROADINGER Flightcase 2x TMH-30/40/60 with wheels
- **PRO flightcase with castors for 2 x TMH-30/TMH-40/TMH-60**
- Developed for 51785980 EUROLITE LED TMH-30 Moving-Head Spot COB, 51785996 EUROLITE LED TMH-40 Moving-Head Wash, 51785984 EUROLITE LED TMH-60 Moving-Head Spot COB or comparable Moving Heads
- Suitable for 2 units
- Interior and cover (not removable) upholstered with foam
- High-quality workmanship with multiplex birch wood, dark brown laminated

Logistic

- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, medium-sized steel ball corners (chrome)
- 4 castors (100 mm), 2 of which with locking brakes
- 4 stacking dishes for stacking the cases
- 2 hinges
- 2 high-quality butterfly locks
- 2 chrome case handles
- For perfect protection
- Castors
- Branded hardware
- Made in Europe

Technical specifications:

Weight:	32.50 kg
---------	----------

EUROLITE LED IP PAR 14x8W QCL

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	90 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	14 x 8 W high-power 4in1 RGBW (homogenous color mix)
Flash rate:	0.5 - 24 Hz
Equipment:	Frost filter
DMX channels:	2; 3; 4; 4; 8
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
PWM frequency:	5900 Hz
Beam angle:	15°
Beam angle (1/2 peak):	15° 27° 30° 60°
Beam angle (1/10 peak):	32°
Housing color:	Black

Attachment system:	Double bracket
Display type:	Monochrome LCD display
Color:	Black
Dimensions:	Width: 31 cm Depth: 22.5 cm Height: 36.5 cm
Weight:	7.15 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

ROADINGER Flightcase 2x TMH-30/40/60 with wheels

Maximum load:	50 kg
Transport aid:	Castors
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	25.5 cm x 31 cm x 31 cm
Accessory compartment:	11.5 cm x 31 cm x 31 cm
Inside dimensions:	67 cm x 31 cm x 31 cm
Dimensions:	Width: 71 cm Depth: 35 cm Height: 53 cm
Weight:	16.00 kg

Scope of delivery:

1 x spotlight
 1 x user manual
 1 x power cord
 1 x remote control
 1 x battery
 3 x frost filter
 1 x XLR cable
 2 x knurled screw