

EUROLITE Set 2x Stage Stand 100cm + 2x LED TMH-60 MK2

2x Stage Stand including 2x LED TMH-60 MK2 moving head

Art. No.: 20000585

GTIN:



Features:

- Compact lightweight
- Equipped with a 60 W COB LED
- 3-facet prism (rotating)
- Preprogrammed scenes in Program Run for stand-alone operation
- Electronic dimmer
- Motorized focus
- Programmable color-change speed and strobe effect
- Exact positioning via 16 bit PAN/TILT movement resolution
- PAN-angle switchable between 540°, 360° and 180° (in sound and auto mode)
- TILT-angle switchable between 270°, 180° and 90° (in sound and auto mode)
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Control board with LC display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT Reverse, Program, Reset
- Switch-mode power supply for operation between 100 and 240 Volts
- 1 LED 60 W COB (chip-on-board) cold white (CW)
- TILT angle switchable between 270° and 180°; and 90°
- PAN angle switchable between 540° and 360°; and 180°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos; gobo wheel with static gobos; prism 3-fold; focus motor-driven
- Gobo effect; beam effect
- Color wheel with 7 dichroic filters plus open
rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 8 gobos and open
- Gobo wheel with rotating gobos, 6 gobos and open
shake effect
- Can be operated in 2; 11; 14 CH mode

Logistic

- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone
- With a beam angle of 14°
- LCD display
- <p>EUROLITE 2x Stage Stand 100cm incl. Cover and Bag, white
- Set with 2 stands for moving heads**
- Translucent stretch fabric - can be backlit with any lighting effect
- Suitable for moving heads with a maximum weight of 30 kg
- Pin (Ø 35 mm) for mounting speakers
- Fast assembly without any tools
- Stand weight 10.7 kg each
- Washable (needs to be treated with flame retardant spray afterwards)
- B1 low flammability
- For application areas such as: Trade fair and shop fitting; wedding/gala/events

Technical specifications:

Weight:	37.80 kg
---------	----------

EUROLITE LED TMH-60 MK2 Moving Head Spot COB

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	135 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	1 x 60 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	270°, 180° exact positioning (16 bit resolution) auto position correction (feedback); , 90°
Max. PAN movement:	540°, 360° exact positioning (16 bit resolution) auto position correction (feedback); , 180°
Equipment:	Gobo wheel with rotating gobos; gobo wheel with static gobos; prism 3-fold; focus motor-driven
Color generation:	Color wheel with 7 dichroic filters plus open Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 8 gobos and open Gobo wheel with rotating gobos, 6 gobos and open Shake effect
DMX channels:	2; 11; 14
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone
Fixtures available for:	Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain
Beam angle:	14°
Beam angle (1/2 peak):	14°

Illuminance in Lux (lx):	Cold white (CW) 1m: 26675 lx, 3m: 3045 lx, 6m: 768 lx
Housing color:	Black
Display type:	LCD display
Dimensions:	Width: 25 cm Depth: 24.5 cm Height: 31.5 cm
Weight:	7.40 kg

EUROLITE 2x Stage Stand 100cm incl. Cover and Bag, white

Maximum load:	30 kg
Material:	Steel
Color:	White
Dimensions:	Width: 50 cm Depth: 50 cm Height: 100 cm
Weight:	22.85 kg
Weight:	10.7 kg

Scope of delivery:

2 x EUROLITE LED TMH-60 MK2 Moving Head Spot COB

1 x moving light
1 x user manual
1 x power cord
1 x XLR cable
2 x omega bracket

1 x EUROLITE 2x Stage Stand 100cm incl. Cover and Bag, white

2 x bag
2 x stand
4 x plate