

EUROLITE Set 2x LED PLL-360 6000K Panel + Case

2x surface light with 360 cold white LEDs and DMX including PRO flightcase

Art. No.: 20000601

GTIN: 4026397659016



Features:

- 4 barn doors to avoid blinding the audience and for protection during transport
 - Frost filter provides a soft, homogeneous light
 - Very high color rendering index (CRI)
 - With a beam angle of 120°
 - Silent operation
 - Flicker-free
 - Dimmable
 - Slim, rugged metal housing
 - Control via quick select potentiometer for brightness; DMX; master/slave function
 - 360 LEDs 0.5 W SMD 2835 cold white (CW)
 - Dimmer electronic; Dimmer speed (step response) adjustable
 - Strobe effect
 - The device is cooled by passive convection cooling
 - With mounting bracket
 - LCD display
 - Rugged carrying handle
 - Mains input and output for power linking up to 8 units
 - Various versions available
 - For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography
 - Application possibility: Suspended; on stand
 - Can be operated in 3 CH mode
 - <p>ROADINGER Flightcase 2x LED PLL-360
- Trunk case, PRO version**
- With accessory compartment
 - With 2 device compartments

Logistic

EAN / GTIN: 4026397659016

Weight: 26,50 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.65 m

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	23.00 kg
---------	----------

EUROLITE LED PLL-360 6000K Panel

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	130 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
Lamp specification:	Dimmable
LED type:	360 x 0.5 W SMD 2835 cold white (CW)
DMX channels:	3
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Quick select potentiometer for brightness; DMX; master/slave function
Fixtures available for:	Light´J; LED PC-Control 512; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	120°
Color temperature:	6000K
Color rendering index (CRI):	94 Ra
Illuminance in Lux (lx):	Warm white (WW) 3m: 498 lx, 6m: 148 lx
Lamp life:	50000 h
Luminous flux:	9937 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Carrying handle:	1 pc/pcs
Dimensions:	Width: 57 cm

	Depth: 12 cm Height: 31 cm
Weight:	6.10 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F
EPREL-Nr:	1056097

ROADINGER Flightcase 2x LED PLL-360

Maximum load:	50 kg
Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm; birch multiplex
Color:	Dark brown, laminated
Accessory compartment:	61 cm x 10.5 cm x 26 cm
Device compartment:	57 cm x 8 cm x 26 cm
Inside dimensions:	61 cm x 26 cm
Dimensions:	Width: 65 cm Depth: 37 cm Height: 48 cm
Weight:	10.80 kg

Scope of delivery:

1 x spotlight
1 x user manual
1 x power cord