

EUROLITE Set 2x LED TMH-75 Hybrid + Case

2x bright spotlight and full-fledged washlight with 75 W LED including PRO flightcase

Art. No.: 20000609

GTIN:



Features:

- Equipped with a white 75 W COB LED and nine 8 W 6in1LEDs in the colors red, green, blue, amber, white and UV
- Compact lightweight
- 7 brilliant, dichroic colors plus white
- Rainbow effect with adjustable speed in both directions
- Gobo-wheel with 6 rotating gobos plus open
- 3-facet prism (rotating)
- Preprogrammed scenes in Program Run for stand-alone operation
- Electronic dimmer
- Motorized focus
- Programmable color-change speed and strobe effect
- Stepless RGBAW+UV color mixture
- Color macros can be called up via DMX controller
- Exact positioning via 16 bit PAN/TILT movement resolution
- PAN-angle switchable between 540°, 360° and 180°
- TILT-angle switchable between 270°, 180° and 90°
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Control board with LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT Reverse, Program, Reset
- Switch-mode power supply for operation between 100 and 240 Volts
- 9 LEDs 8 W high-power 6in1 RGBWA/UV (homogenous color mix)
- 1 LED 75 W COB (chip-on-board) cold white (CW)
- TILT angle switchable between 270° and 180°; and 90°
- PAN angle switchable between 540° and 360°; and 180°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)

Logistic

- Gobo wheel with rotating gobos; prism 3-fold; focus motor-driven
- Gobo effect; beam effect
- Color wheel with 7 dichroic filters plus open
- Gobo wheel with rotating gobos, 6 gobos and open
- Can be operated in 21 CH mode
- The device is cooled by cooling fan
- Control via DMX; sound to light via microphone
- With a beam angle of 12° spot
- <p>ROADINGER Flightcase 2x LED TMH-75
- **Trunk case with castors, HIGHLINE version**
- With 1 Inlet tray for labeling panel
- High-quality workmanship with birch multiplex 9 mm,
- Interior with foam padding
cover with foam padding
- Removable cover
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 4 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	41.40 kg
---------	----------

EUROLITE LED TMH-75 Hybrid Moving-Head Spot/Wash COB

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	9 x 8 W high-power 6in1 RGBWA/UV (homogenous color mix) 1 x 75 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	270°, 180° exact positioning (16 bit resolution) auto position correction (feedback); , 90°
Max. PAN movement:	540°, 360° exact positioning (16 bit resolution) auto position correction (feedback); , 180°
Equipment:	Gobo wheel with rotating gobos; prism 3-fold; focus motor-driven
Color generation:	Color wheel with 7 dichroic filters plus open
Gobos:	Gobo wheel with rotating gobos, 6 gobos and open
DMX channels:	21
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; sound to light via microphone

Fixtures available for:	Light J; LED PC-Control 512; EASY SHOW 1; Light Captain
Beam angle:	12° spot
Beam angle (1/2 peak):	Spot 12° Wash effect 28°
Beam angle (1/10 peak):	45°
Illuminance in Lux (lx):	Wash effect red (R) 3m: 24 lx, 6m: 7 lx Wash effect green (G) 3m: 133 lx, 6m: 36 lx Wash effect blue (B) 3m: 20 lx, 6m: 6 lx Wash effect cold white (CW) 3m: 92 lx, 6m: 26 lx Wash effect amber (A) 3m: 31 lx, 6m: 9 lx Wash effect ultra violet (UV) 3m: 1 lx, 6m: 1 lx Wash effect all 3m: 288 lx, 6m: 78 lx Spot cold white (CW) 3m: 3942 lx, 6m: 1008 lx
Housing color:	Black
Dimensions:	Width: 25.5 cm Depth: 25 cm Height: 31 cm
Weight:	8.20 kg

ROADINGER Flightcase 2x LED TMH-75

Maximum load:	50 kg
Removable covers:	1 pc/pcs
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Lock:	Butterfly lock: 4 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 9 mm
Accessory compartment:	60.5 cm x 10.5 cm x 39 cm
Device compartment:	29 cm x 25 cm x 37 cm
Inside dimensions:	60.5 cm x 39.5 cm x 39 cm
Dimensions:	Length: 65 cm Depth: 44 cm Height: 73.5 cm
Weight:	25.10 kg

Scope of delivery:

1 x moving light
2 x omega bracket
4 x screw
1 x user manual
1 x power cord
1 x XLR cable