

EUROLITE Set LED SL-600 DMX Search Light + Case

Follow spot with cold white 600 W LED including PRO flightcase

Art. No.: 20000610

GTIN: 4026397659108



List price: 4044.81 €

incl. 19% VAT.

Features:

- Manual control via movable control panel with buttons and faders
- 1 LED 600 W COB (chip-on-board) cold white (CW)
- Focus manual; iris stepless
- Dimmer electronic
- Strobe effect
- Color wheel with 7 dichroic filters plus open
half colors selectable
- Can be operated in 5 CH mode
- The device is cooled by cooling fan
- Control via DMX
- Flicker-free
- With a beam angle of 7° - 13°
- Direct color temperature selection for 3 preset values
- With mounting bracket
- LCD display
- Built with SEETRONIC connector
- Suitable for a range of use from 50 to 100 meters
- For application areas such as: Wedding/gala/events; stage; theater; rental
- Application possibility: On stand
- <p>ROADINGER Flightcase 1x LED SL-600
- **Trunk case, PRO version**
- With 1 device compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 3 chrome tip-over locks

Logistic

EAN / GTIN: 4026397659108

Weight: 37,30 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.50 m

Bulky product

- 2 high-quality butterfly locks
- Closes with a
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	35.00 kg
---------	----------

EUROLITE LED SL-600 DMX Search Light

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	640 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 5 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 600 W COB (chip-on-board) cold white (CW)
Flash rate:	0.8 - 16 Hz
Equipment:	Focus manual; iris stepless
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable
DMX channels:	5
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX
Fixtures available for:	LED PC-Control 512; Light Captain
Projection:	Flicker-free
PWM frequency:	26600 Hz
Beam angle:	7° - 13°
Beam angle (1/2 peak):	7 - 13°
Beam angle (1/10 peak):	7 - 13°
Color temperature:	6500K
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Use of brands:	Built with SEETRONIC connector
Range of use:	50m - 100m
Dimensions:	Length: 105 cm Width: 23 cm Height: 34 cm
Weight:	18.50 kg

Noise classification:	Class 3 (clearly perceptible sounds)
-----------------------	--------------------------------------

ROADINGER Flightcase 1x LED SL-600

Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Inside dimensions:	109 cm x 38.5 cm x 36 cm
Device compartment:	105 cm x 38.5 cm x 36 cm
Dimensions:	Width: 113 cm Depth: 43 cm Height: 42 cm
Weight:	13.60 kg

Scope of delivery:

1 x spotlight
1 x user manual
1 x power cord