

OMNITRONIC Set MOM-10BT4 Receiver module + Bodypack transmitter + Lavalier microphone

GTIN:



The article is no longer in our assortment.

Features:

Logistic

OMNITRONIC MOM-10BT4 Receiver Module

Receiver module for UHF frequencies (microphone, bodypack + audio link module)

- For retrofitting the MOM-10BT4 modular PA system
- Up to 4 receiving modules can be retrofitted
- 16 selectable UHF frequencies (823-832 and 863-865 MHz)
- LEDs for power, carrier and audio signals
- Operating range up to 30m with line-of-sight
- UHF 823 - 832 MHz License-free and approved in large parts of Europe
- UHF 863 - 865 MHz License-free and approved in Europe

OMNITRONIC MOM-10BT4 Bodypack Transmitter

Bodypack transmitter with 16 UHF frequencies (823-832 & 863-865 MHz)

- 16 selectable UHF frequencies (823-832 and 863-865 MHz)
- Sensitivity adjustable
- LED indicator for battery capacity
- Belt clip
- Headset microphone and lavalier microphone available as accessories
- Operating range up to 30m with line-of-sight
- UHF 823 - 832 MHz License-free and approved in large parts of Europe
- UHF 863 - 865 MHz License-free and approved in Europe

- LCD display
- Charge status indicator

OMNITRONIC MOM-10BT4 Lavalier Microphone

Black, inconspicuous tie-clip microphone

- For attaching to the user's tie, shirt or collar
- Low weight
- Polar pattern: Cardioid
- For application areas such as: Theater; product presentations and lectures

Technical specifications:

Weight:	0.22 kg
---------	---------

OMNITRONIC MOM-10BT4 Receiver Module

Type:	Receiver
Power supply:	12V DC 150 mA
Frequency range:	50 - 15000 Hz
S/N ratio:	>80 dB
THD:	<0.1 % at 1 kHz
Sensitivity:	-95 dB
Range:	Range up to 30m with line-of-sight
Frequency band:	UHF 823 - 832 MHz; UHF 863 - 865 MHz
Frequency stability:	± 0.01 %
Frequency selection:	16 switchable frequencies
Control elements:	Frequency selector switch, level control
Dimensions:	Width: 7.1 cm Depth: 13.9 cm Height: 3 cm
Weight:	0.09 kg

OMNITRONIC MOM-10BT4 Bodypack Transmitter

Type:	Pocket transmitter
Power supply:	3V DC
Power connection:	Battery/battery pack
Battery:	2 x Mignon (AA) (not included)
Range:	Range up to 30m with line-of-sight
Frequency band:	UHF 823 - 832 MHz; UHF 863 - 865 MHz
Frequency stability:	± 0.01 %
RF power output:	10 mW
Frequency selection:	16 switchable frequencies
Connector type:	Mini XLR (M) 3-pin mounting version
Display type:	LCD display

Display reading:	Channel , charge status indicator
Switch:	On/off switch
Material:	Plastic
Dimensions:	Width: 6.6 cm Depth: 2.2 cm Height: 10.8 cm
Weight:	0.10 kg

OMNITRONIC MOM-10BT4 Lavalier Microphone

Type:	Lavalier microphone
Power supply:	1.5-10V DC
Power connection:	Mains input via Mini XLR (F) 3-pin
Cable length:	1 m
Capsule type:	Condenser
Polar pattern:	Cardioid
Frequency range:	50 - 20000 Hz
Sensitivity:	-37 dB
Max. SPL:	120 dB
Material:	Metal
Color:	Black
Weight:	0.03 kg

Scope of delivery:

1 x OMNITRONIC MOM-10BT4 Receiver Module

1 x receiver
1 x user manual
1 x declaration of conformity

1 x OMNITRONIC MOM-10BT4 Bodypack Transmitter

1 x transmitter
1 x user manual
1 x declaration of conformity

1 x OMNITRONIC MOM-10BT4 Lavalier Microphone

1 x microphone