

EUROLITE Set 4x LED TL-4 Trusslight + Case

4x variable truss light and uplight with bright 4 x 8 W RGB+UV LED incl. case

Art. No.: 20000638

GTIN: 4026397663808



List price: 593.81 €

incl. 19% VAT.

Features:

- Compact and bright
- Perfect for ALUTRUSS 4 point system QUADLOCK
- Folding foot adjustable in 5 steps for flexible placement
- 4 LEDs 8 W high-power 4in1 RGB/UV (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Integrated show programs
- Direct color selection for 18 preset colors
- Can be operated in 3; 4; 8 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone
- With a beam angle of 13°
- Monochrome 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended
- <p>ROADINGER TDV-1 Universal Case Pick
- **Universal case with flexible foam dividers**
- With dividers
- High-quality workmanship with plastic 3 mm, black, imprinted
- Interior with foam padding

Logistic

EAN / GTIN: 4026397663808

Weight: 11,50 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.52 m

- Aluminum profile frames 12mm with rounded edges
- Rugged carrying handle
- 3 chrome tip-over locks
- 2 high-quality spring locks with shut-off function
- Closes with a
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	9.69 kg
---------	---------

EUROLITE LED TL-4 QCL RGB+UV Trusslight

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	15 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	4 x 8 W high-power 4in1 RGB/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 8
DMX input:	1 x USB, type A 1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone
Fixtures available for:	LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Beam angle:	13°
Beam angle (1/2 peak):	13°
Beam angle (1/10 peak):	30°
Housing color:	Black
Attachment system:	M10 thread
Display type:	Monochrome 4 digit 7-segment LED display
Transport aid:	Rubber feet
Dimensions:	Length: 15.5 cm Width: 14.5 cm Height: 13.0 cm
Weight:	1.56 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0

Cable construction:	3 x 0.75 mm² H05VV-F
Cable length:	Approx. 1.1 m
Color:	Black

ROADINGER TDV-1 Universal Case Pick

Maximum load:	25 kg
Aluminum profile frames:	12 mm
Carrying handle:	1 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Spring lock: 2 pc/pcs with shut-off function
Material:	Plastic, 3 mm
Color:	Black, imprinted
Inside dimensions:	52 cm x 28.5 cm x 20 cm
Dimensions:	Width: 54 cm Depth: 31 cm Height: 26 cm
Weight:	3.45 kg

Scope of delivery:

4 x EUROLITE LED TL-4 QCL RGB+UV Trusslight

1 x spotlight
1 x power cord
1 x remote control
1 x user manual

1 x ROADINGER TDV-1 Universal Case Pick

1 x case