

EUROLITE Set 4x AKKU TL-3 TCL white + Case TDV-1

4x white spot for lighting within trussing, 3 x 3 W 3in1 LED including case

Art. No.: 20000651

GTIN: 4026397670882



List price: 910.35 €

incl. 19% VAT.

Features:

- Compact and bright
 - Ideal for ALUTRUSS DECOLOCK DQ3 3-point system
 - Integrated QuickDMX transceiver for wireless DMX control
 - Threaded inserts for suspended installation
 - Cordless, flexible and versatile
 - Battery operation up to 16h depending on program used
 - 3 LEDs 3 W SMD 8072 3in1 RGB (homogenous color mix)
 - Dimmer electronic; color blend stepless; color change adjustable; Dimmer speed (step response) adjustable
 - Strobe effect
 - Can be operated in 3; 5; 8 CH mode
 - The device is cooled by passive convection cooling
 - Control via IR remote control; DMX; QuickDMX; sound to light via microphone; stand-alone
 - Flicker-free
 - With a beam angle of 11°
 - Multicolor LCD display
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; rental; advertisement/Shop window
 - Silent operation
 - Application possibility: Standing; suspended
 - <p>ROADINGER TDV-1 Universal Case Pick
- Universal case with flexible foam dividers**
- With dividers
 - High-quality workmanship with plastic 3 mm, black, imprinted
 - Interior with foam padding

Logistic

EAN / GTIN: 4026397670882

Weight: 10,00 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.35 m

- Aluminum profile frames 12mm with rounded edges
- Rugged carrying handle
- 3 chrome tip-over locks
- 2 high-quality spring locks with shut-off function
- Closes with a
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	8.65 kg
---------	---------

EUROLITE AKKU TL-3 TCL Trusslight QuickDMX wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
Power connection:	Battery/battery pack Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Battery pack type:	1 x lithium ion 11.1 V, 4400 mAh, 48.84 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED type:	3 x 3 W SMD 8072 3in1 RGB (homogenous color mix)
Flash rate:	0 - 23 Hz
DMX channels:	3; 5; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; DMX; QuickDMX; sound to light via microphone; stand-alone
Fixtures available for:	Light´J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle:	11°
Beam angle (1/2 peak):	11°
Beam angle (1/10 peak):	24°
Housing color:	White
Display type:	Multicolor LCD display
Dimensions:	Width: 12.1 cm Depth: 10.8 cm Height: 14.5 cm
Weight:	1.30 kg

Noise classification:	Class 0 (no noise at all)
Cable construction:	3 x 1.0 mm² H05VV-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

ROADINGER TDV-1 Universal Case Pick

Maximum load:	25 kg
Aluminum profile frames:	12 mm
Carrying handle:	1 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Spring lock: 2 pc/pcs with shut-off function
Material:	Plastic, 3 mm
Color:	Black, imprinted
Inside dimensions:	52 cm x 28.5 cm x 20 cm
Dimensions:	Width: 54 cm Depth: 31 cm Height: 26 cm
Weight:	3.45 kg

Scope of delivery:

4 x EUROLITE AKKU TL-3 TCL Trusslight QuickDMX wh

1 x spotlight
 1 x user manual
 1 x power cord
 1 x remote control
 1 x battery
 1 x declaration of conformity

1 x ROADINGER TDV-1 Universal Case Pick

1 x case