

EUROLITE Set 2x LED IP PAR 14x10W HCL + Case

2x weather-proof spotlight with RGBAW+UV color mixing and frost filters incl. PRO flightcase

Art. No.: 20000655

GTIN: 4026397670929



The article is no longer in our assortment.

Features:

- 14 LEDs 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
- Frost filter
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 25 preset colors
- Can be operated in 3; 5; 6; 8; 12 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- For application areas such as: Architecture; stage; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand
- <p>ROADINGER Flightcase 2x TMH-30/40/60
- **PRO flightcase for 2 x EUROLITE LED TMH-30/TMH-40/TMH-60 moving head**
- For optimal security
- With 2 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles

Logistic

EAN / GTIN: 4026397670929

Weight: 25,50 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.75 m

Bulky product

- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	22.80 kg
---------	----------

EUROLITE LED IP PAR 14x10W HCL

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	95 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	14 x 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
Equipment:	Frost filter
DMX channels:	3; 5; 6; 8; 12
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; IR remote control
Fixtures available for:	Light´J; LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light´J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15° 27° 30° 60°
Housing color:	Black matte
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 31 cm Depth: 22.5 cm Height: 36.5 cm

Weight:	6.80 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 3 mm
Cable construction:	3 x 1.0 mm² H05RN-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Material:	Plastic, 2 mm
Dimensions:	Diameter: Ø 20.5 cm
Cable length:	Approx. 1.5 m

ROADINGER Flightcase 2x TMH-30/40/60

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	26.5 cm x 31 cm x 30.5 cm
Middle compartment:	10.5 cm x 31 cm x 30.5 cm
Inside dimensions:	63.5 cm x 31 cm x 30.5 cm
Dimensions:	Width: 71 cm Depth: 35 cm Height: 40.5 cm
Weight:	9.20 kg

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x remote control
- 3 x frost filter
- 1 x XLR cable
- 2 x knurled screw
- 1 x user manual