

## EUROLITE Set 2x LED BAR-12 UV Bar + Soft Bag

2x Light effect bar (1 m) with UV LEDs including soft bag

Art. No.: 20000661

GTIN: 4026397671001



### Features:

- 12 LEDs 1 W high-power ultra violet (UV)
- Dimmer electronic
- UV effect
- Can be operated in 1; 2 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 14°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; party room; restaurants, bars and hotels
- Silent operation
- Application possibility: Suspended; wall mounting
- <p>EUROLITE SB-12 Soft Bag
- **Practical black soft bag for LED bars (1 m length), adjustable divider**
- Ideal for 1 or 2 LED bars with 1 meter length
- Made of easy-care nylon
- With divider
- With 2 device compartments
- High-quality workmanship with textile , black
- Interior with foam padding
- 2 carrying straps
- 1 x shoulder strap

### Logistic

EAN / GTIN: 4026397671001

Weight: 8,00 kg

Length: 1.10 m

Width: 0.50 m

Heigh: 0.20 m

## Technical specifications:

---

|         |         |
|---------|---------|
| Weight: | 5.90 kg |
|---------|---------|

---

### EUROLITE LED BAR-12 UV Bar

|                          |                                                                                                                                                                                           |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:            | 100-240 V AC, 50/60 Hz                                                                                                                                                                    |
| Power consumption:       | 25 W                                                                                                                                                                                      |
| Protection class:        | Protection class I                                                                                                                                                                        |
| Power connection:        | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)                                                                                          |
| Power output:            | IEC connector (F) mounting version                                                                                                                                                        |
| Lamp type:               | LED lamp                                                                                                                                                                                  |
| LED type:                | 12 x 1 W high-power ultra violet (UV)                                                                                                                                                     |
| DMX channels:            | 1; 2                                                                                                                                                                                      |
| Cooling:                 | Passive convection cooling                                                                                                                                                                |
| Control:                 | DMX; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for:  | Colorchief                                                                                                                                                                                |
| Projection:              | Flicker-free                                                                                                                                                                              |
| Beam angle:              | 14°                                                                                                                                                                                       |
| Beam angle (1/2 peak):   | 14°                                                                                                                                                                                       |
| Beam angle (1/10 peak):  | 24°                                                                                                                                                                                       |
| Housing color:           | Black                                                                                                                                                                                     |
| Attachment system:       | Mounting bracket                                                                                                                                                                          |
| Display type:            | 4 digit 7-segment LED display                                                                                                                                                             |
| Dimensions:              | Length: 100 cm<br>Depth: 8.5 cm<br>Height: 11.5 cm                                                                                                                                        |
| Weight:                  | 2.65 kg                                                                                                                                                                                   |
| Noise classification:    | Class 0 (no noise at all)                                                                                                                                                                 |
| Photobiological safety:  | Risk Group 0                                                                                                                                                                              |
| Cable construction:      | 3 x 0.75 mm² H05VV-F                                                                                                                                                                      |
| Cable length:            | Approx. 1.1 m                                                                                                                                                                             |
| Diameter mounting holes: | 1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø7mm                                                                                                                                                  |
| Material:                | Metal, 2 mm                                                                                                                                                                               |

### EUROLITE SB-12 Soft Bag

|               |       |
|---------------|-------|
| Maximum load: | 20 kg |
|---------------|-------|

---

|                 |                                                |
|-----------------|------------------------------------------------|
| Carrying strap: | 2 pc/pcs                                       |
| Transport aid:  | 1 x shoulder strap                             |
| Material:       | Textile                                        |
| Color:          | Black                                          |
| Dimensions:     | Width: 107 cm<br>Depth: 17 cm<br>Height: 18 cm |
| Weight:         | 0.60 kg                                        |

**Scope of delivery:**

- 1 x light effect
- 1 x power cord
- 2 x mounting bracket
- 2 x knurled screw
- 2 x washer
- 1 x user manual