

## EUROLITE Set 2x LED BAR-12 QCL RGB+UV Bar + Soft Bag

2x light effect bar (1 m) with RGB+UV color mixing including soft bag

Art. No.: 20000663

GTIN: 4026397671025



### Features:

- 12 LEDs 4 W high-power 4in1 RGB/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- Integrated show programs
- Direct color selection for 20 preset colors
- Can be operated in 2; 4; 5; 6; 9 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 20°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; wall mounting
- **screw**
- M8 thread
- **EUROLITE SB-12 Soft Bag**
- **Practical black soft bag for LED bars (1 m length), adjustable divider**
- Ideal for 1 or 2 LED bars with 1 meter length
- Made of easy-care nylon
- With divider

### Logistic

EAN / GTIN: 4026397671025

Weight: 8,00 kg

Length: 1.10 m

Width: 0.50 m

Height: 0.30 m

- With 2 device compartments
- High-quality workmanship with textile , black
- Interior with foam padding
- 2 carrying straps
- 1 x shoulder strap

## Technical specifications:

|         |         |
|---------|---------|
| Weight: | 6.30 kg |
|---------|---------|

### EUROLITE LED BAR-12 QCL RGB+UV Bar

|                         |                                                                                                                                                                                           |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                                                                                    |
| Power consumption:      | 25 W                                                                                                                                                                                      |
| Protection class:       | Protection class I                                                                                                                                                                        |
| Power connection:       | Mains input via IEC connector (M) mounting version power supply cord with safety plug included                                                                                            |
| Power output:           | 1 x IEC connector (F) mounting version                                                                                                                                                    |
| Lamp type:              | LED lamp                                                                                                                                                                                  |
| LED type:               | 12 x 4 W high-power 4in1 RGB/UV (homogenous color mix)                                                                                                                                    |
| Flash rate:             | 0 - 20 Hz                                                                                                                                                                                 |
| DMX channels:           | 2; 4; 5; 6; 9                                                                                                                                                                             |
| DMX input:              | 3-pin XLR (M) mounting version                                                                                                                                                            |
| DMX output:             | 3-pin XLR (F) mounting version                                                                                                                                                            |
| Cooling:                | Passive convection cooling                                                                                                                                                                |
| Control:                | Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for: | LED PC-Control 512; EASY SHOW 2; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief                                                                                                      |
| Projection:             | Flicker-free                                                                                                                                                                              |
| Beam angle:             | 20°                                                                                                                                                                                       |
| Beam angle (1/2 peak):  | 20°                                                                                                                                                                                       |
| Beam angle (1/10 peak): | 33°                                                                                                                                                                                       |
| Wavelength:             | Ultra violet (UV) 399 nm                                                                                                                                                                  |
| Housing color:          | Black                                                                                                                                                                                     |
| Attachment system:      | Mounting bracket                                                                                                                                                                          |
| Display type:           | 4 digit 7-segment LED display                                                                                                                                                             |
| Material:               | Aluminum; metal                                                                                                                                                                           |
| Dimensions:             | Length: 100 cm<br>Depth: 6.5 cm<br>Height: 10.3 cm                                                                                                                                        |

|                          |                                    |
|--------------------------|------------------------------------|
| Weight:                  | 2.85 kg                            |
| Noise classification:    | Class 0 (no noise at all)          |
| Photobiological safety:  | Risk Group 0                       |
| Cable construction:      | 3 x 0.75 mm² H05VV-F               |
| Cable length:            | 1.2 m                              |
| Diameter mounting holes: | 1 x Ø20mm; 1 x Ø11mm; 2 x Ø7mm     |
| Material:                | Metal, 2 mm                        |
| Thread:                  | M8 thread x 16 mm                  |
| Material:                | Rubber                             |
| Dimensions:              | Height: 0.3 cm<br>Diameter: Ø 2 cm |

**EUROLITE SB-12 Soft Bag**

|                 |                                                |
|-----------------|------------------------------------------------|
| Maximum load:   | 20 kg                                          |
| Carrying strap: | 2 pc/pcs                                       |
| Transport aid:  | 1 x shoulder strap                             |
| Material:       | Textile                                        |
| Color:          | Black                                          |
| Dimensions:     | Width: 107 cm<br>Depth: 17 cm<br>Height: 18 cm |
| Weight:         | 0.60 kg                                        |

**Scope of delivery:**

- 1 x bar
- 1 x power cord
- 2 x mounting bracket
- 2 x screw
- 2 x washer
- 1 x user manual