

EUROLITE Set 4x LED BAR-12 QCL RGB+UV Bar + Case

4x light effect bar (1 m) with RGB+UV color mixing including flightcase

Art. No.: 20000664

GTIN: 4026397671032



Features:

- 12 LEDs 4 W high-power 4in1 RGB/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- Integrated show programs
- Direct color selection for 20 preset colors
- Can be operated in 2; 4; 5; 6; 9 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 20°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; wall mounting
- screw**
- M8 thread
- <p>ROADINGER Flightcase EC-B252 4x LED BAR-252 RGB
- Carrying case**
- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges

Logistic

EAN / GTIN: 4026397671032

Weight: 26,50 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.60 m

Bulky product

- Rugged carrying handle
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	22.30 kg
---------	----------

EUROLITE LED BAR-12 QCL RGB+UV Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	12 x 4 W high-power 4in1 RGB/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	LED PC-Control 512; EASY SHOW 2; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	33°
Wavelength:	Ultra violet (UV) 399 nm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum; metal
Dimensions:	Length: 100 cm Depth: 6.5 cm Height: 10.3 cm

Weight:	2.85 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Cable construction:	3 x 0.75 mm² H05VV-F
Cable length:	1.2 m
Diameter mounting holes:	1 x Ø20mm; 1 x Ø11mm; 2 x Ø7mm
Material:	Metal, 2 mm
Thread:	M8 thread x 16 mm
Material:	Rubber
Dimensions:	Height: 0.3 cm Diameter: Ø 2 cm

ROADINGER Flightcase EC-B252 4x LED BAR-252 RGB

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Carrying handle:	1 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Material:	Plywood multi-layer glued, 7 mm
Color:	Black, laminated
Inside dimensions:	108 cm x 44 cm x 7.5 cm
Device compartment:	108 cm x 6.5 cm x 7.5 cm
Dimensions:	Width: 117 cm Depth: 48 cm Height: 17 cm
Weight:	10.90 kg

Scope of delivery:

- 1 x bar
- 1 x power cord
- 2 x mounting bracket
- 2 x screw
- 2 x washer
- 1 x user manual