

EUROLITE Set 8x LED PAR-64 COB RGBW 120W Zoom bk + Case

8x PAR spot with 120 W RGBW LED and manual zoom incl. flightcase with castors

Art. No.: 20000669

GTIN: 4026397126594



The article is no longer in our assortment.

Features:

- 1 LED 120 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
- Color blend stepless; dimmer curves with adjustable response; pulse-width modulation variable
- 3 integrated show programs
- Can be operated in 2; 4; 5; 9; 6 CH mode
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function
- Flicker-free
- With a beam angle of 11° - 48°
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage
- <p>ROADINGER Flightcase 8x PAR-64/ML-56

Trunk case with castors

- With 8 device compartments
- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding
cover with felt cover
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EAN / GTIN: 4026397126594

Weight: 85,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 1.20 m

Bulky product

Technical specifications:

Weight:	72.90 kg
---------	----------

EUROLITE LED PAR-64 COB RGBW 120W Zoom bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	140 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version
Fuse:	F 2 A
Lamp type:	LED lamp
LED type:	1 x 120 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 9; 6
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	11° - 48°
Beam angle (1/2 peak):	11 - 35°
Beam angle (1/10 peak):	15 - 48°
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Width: 26 cm Depth: 43.5 cm Height: 37.5 cm
Weight:	3.90 kg
Noise classification:	Class 2 (slight noise)

ROADINGER Flightcase 8x PAR-64/ML-56

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs

Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Material:	Plywood multi-layer glued, 9 mm
Color:	Black, laminated
Device compartment:	24 cm x 24.5 cm x 42 cm
Inside dimensions:	96 cm x 49 cm x 42 cm
Dimensions:	Width: 109 cm
	Depth: 57.5 cm
	Height: 68.5 cm
Weight:	41.70 kg

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x XLR cable
- 1 x filter frame
- 1 x mounting bracket
- 2 x knurled screw
- 2 x washer