

EUROLITE Set LED IP PAR 7x8W QCL Spot + 2x Diffuser Cover (15x60° and 40°): 20000670

Weather-proof spotlight with 7 4in1 RGBW LEDs and RGBW color mixing incl. 2x frost filters

GTIN: 4026397362312



Features:

- 7 LEDs 8 W high-power 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 25 preset colors
- Can be operated in 3; 4; 5; 6; 10 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand
- <p>EUROLITE Diffuser Cover 40° for IP PAR-7
- With a beam angle of 40°

Logistic

EAN / GTIN: 4026397362312

Weight: 5,20 kg

Length: 0.41 m

Width: 0.31 m

Height: 0.28 m

Technical specifications:

Weight:	4.27 kg
EUROLITE LED IP PAR 7x8W QCL Spot	
Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	55 W
IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	7 x 8 W high-power 4in1 RGBW (homogenous color mix)
Flash rate:	0.5 - 24 Hz
DMX channels:	3; 4; 5; 6; 10
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; IR remote control
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
PWM frequency:	5800 Hz
Beam angle:	15°
Beam angle (1/2 peak):	15°
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 25.5 cm Depth: 15.3 cm Height: 28.1 cm
Weight:	4.07 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 2.5 mm
Cable construction:	3 x 1.0 mm² H05RN-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

EUROLITE Diffuser Cover 15x60° for IP PAR-7

Dimensions:	Height: 0.65 cm Diameter: Ø 18.50 cm
Weight:	0.10 kg

EUROLITE Diffuser Cover 40° for IP PAR-7

Beam angle:	40°
Beam angle (1/2 peak):	40°
Dimensions:	Depth: 0.6 cm Diameter: Ø 18.50 cm
Weight:	0.10 kg
Material:	Plastic
Color:	Black
Ring diameter:	Inside: 157 mm

Scope of delivery:

1 x EUROLITE LED IP PAR 7x8W QCL Spot

1 x light effect
1 x mounting bracket
1 x power cord
1 x remote control
1 x user manual

1 x EUROLITE Diffuser Cover 15x60° for IP PAR-7

1 x beamshaper

1 x EUROLITE Diffuser Cover 40° for IP PAR-7

1 x frost filter