

EUROLITE Set 4x LED IP Tourlight 120 QCL + Case

4x weather-proof LED spot with 120 W RGBW LED including PRO flightcase

Art. No.: 20000674

GTIN: 4026397360417



Features:

- High-performance LED spot for outdoor applications
 - Equipped with a 120-watt RGBW COB LED
 - Chip-on-board technology makes for homogeneous color mixing
 - Beam angle: 11° (1/2 peak), 26° (1/10 peak)
 - For architectural and stage lighting
 - Weather-proof metal housing (IP65)
 - Stepless RGBW color blend, color change, color fade, dimmer and strobe effect
 - 63 integrated color macros
 - User-defined color settings can be set and saved individually
 - Different dimmer curves and dimmer speeds (step response) adjustable
 - DMX-controlled operation or stand-alone operation with master/slave function
 - Addressing and setting via control board with four touch operating buttons and LCD
 - Swivel mounting bracket
 - Additional bracket for floor use
 - Hanging installation via quick-lock Omega holder (included in delivery)
 - IP T-Con terminals for power linking up to 8 units
 - 1 LED 120 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
 - Can be operated in 1; 4; 8; 9 CH mode
 - The device is cooled by temperature-controlled fan
 - Control via master/slave function; stand-alone
 - Flicker-free
 - With a beam angle of 11°
 - Suitable for outdoor use IP65
 - <p>ROADINGER Flightcase 4x LED IP Tourlight 120
- Trunk case, PRO version**
- For optimal security

Logistic

EAN / GTIN: 4026397360417

- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	36.25 kg
---------	----------

EUROLITE LED IP Tourlight 120 QCL

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	125 W
IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	1 x 120 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
Flash rate:	1 - 20 Hz
DMX channels:	1; 4; 8; 9
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Temperature-controlled fan
Control:	Master/slave function; stand-alone
Fixtures available for:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Projection:	Flicker-free
Beam angle:	11°
Beam angle (1/2 peak):	11°
Beam angle (1/10 peak):	26°
Housing color:	Black
Dimensions:	Width: 27 cm Depth: 27 cm Height: 30.5 cm
Weight:	5.90 kg

ROADINGER Flightcase 4x LED IP Tourlight 120

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	28 cm x 19 cm x 30.5 cm
Middle compartment:	10.5 cm x 41 cm x 30.5 cm
Inside dimensions:	66.5 cm x 41 cm x 30.5 cm
Dimensions:	Width: 74 cm Depth: 40 cm Height: 45 cm
Weight:	12.65 kg

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x omega bracket
- 1 x cover