

EUROLITE Set 4x Multiflood Pro IP RGBW Wash/Frost + Case

4x bright LED outdoor spot with wireless DMX receiver incl. PRO flightcase

Art. No.: 20000677

GTIN: 4026397360929



The article is no longer in our assortment.

Features:

- Washlight and strobe
- Suitable for external use (IP65)
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- 36 high-power 15 W RGBW LEDs (4in1)
- 16° standard beam angle
- 2 frost filters (25° and 45°) for a softer light with larger beam angles, included in delivery
- Flicker-free projection
- Direct color selection for 20 preset colors
- Stepless RGBW color blend
- Dimmer speed (step response) adjustable
- Addressing and setting via control panel with LED screen and four operating buttons
- Swivel mounting bracket with locking possibility
- Hanging installation via quick-lock Omega holders
- Additional rubber feet protect the device when positioned on the ground
- IP T-Con terminals for power linking up to 8 units
- 36 LEDs 15 W high-power 4in1 RGBW (homogenous color mix)
- Can be operated in 4; 5; 8 CH mode
- The device is cooled by cooling fan
- Control via W-DMX by wireless solution; sound to light via microphone; master/slave function; DMX; stand-alone
- With a beam angle of 16°
- Suitable for outdoor use IP65
- <p>ROADINGER Flightcase 4x Multiflood Pro
- **Trunk case with castors, HIGHLINE version**
- With 4 device compartments
- High-quality workmanship with birch multiplex 9.8 mm, black, laminated

Logistic

EAN / GTIN: 4026397360929

- Interior with foam padding
- Cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 4 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	83.55 kg
---------	----------

EUROLITE Multiflood Pro IP RGBW Wash/Frost

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	215 W
IP classification:	IP65
Protection class:	Protection class I
Lamp type:	LED lamp
LED type:	36 x 15 W high-power 4in1 RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	4; 5; 8
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Cooling fan
Control:	W-DMX by wireless solution; sound to light via microphone; master/slave function; DMX; stand-alone
Fixtures available for:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; GDTF (GrandMA3)
Carrier frequency:	2.4 GHz
Beam angle:	16°
Beam angle (1/2 peak):	16° 25° 45°
Beam angle (1/10 peak):	35°
Housing color:	Black
Dimensions:	Length: 16 cm Width: 49 cm Height: 32 cm
Weight:	12.05 kg
Noise classification:	Class 3 (clearly perceptible sounds)

ROADINGER Flightcase 4x Multiflood Pro

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	4 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 9.8 mm; birch multiplex
Color:	Black, laminated; dark brown, laminated
Device compartment:	21.5 cm x 55.5 cm x 28 cm
Accessory compartment:	11.5 cm x 53.5 cm x 28 cm
Inside dimensions:	105.5 cm x 56 cm x 37 cm
Dimensions:	Width: 110 cm
	Depth: 61 cm
	Height: 53 cm
Weight:	35.35 kg

Scope of delivery:

1 x spotlight
1 x user manual
1 x declaration of conformity
1 x power cord
1 x XLR cable
1 x omega bracket
2 x frost filter
1 x plug (male)