

## EUROLITE Set 4x LED 4C-12 Silent Slim Spot + Case

4x inaudible 4in1 spotlight with RGBW color mixture including PRO flightcase

Art. No.: 20000683

GTIN: 4026397360998



**List price: 1522.01 €**

incl. 19% VAT.

### Features:

- Flat version requires minimal space when mounting
- 12 LEDs 8 W high-power 4in1 RGBW (homogenous color mix)
- Color blend stepless; Dimmer stepless
- Strobe effect
- Integrated show programs
- Direct color selection for 19 preset colors
- Can be operated in 3; 4; 5; 6; 9 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; IR remote control; stand-alone; QuickDMX via USB (optional); sound to light via microphone; master/slave function
- With a beam angle of 16°
- With double bracket
- Monochrome 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Theater; stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; rental; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended; on stand
- <p>ROADINGER Flightcase 4x LED 4/7C-12 Silent Slim Spot
- **Trunk case, PRO version**
- High-quality workmanship with birch multiplex , dark brown, laminated
- Interior with foam padding
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks

### Logistic

EAN / GTIN: 4026397360998

Weight: 27,10 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

- Closes with a
- Branded hardware
- Made in Europe

## Technical specifications:

|         |          |
|---------|----------|
| Weight: | 25.00 kg |
|---------|----------|

### EUROLITE LED 4C-12 Silent Slim Spot

|                         |                                                                                                                                                                        |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                                                                 |
| Power consumption:      | 55 W                                                                                                                                                                   |
| Protection class:       | Protection class I                                                                                                                                                     |
| Power connection:       | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)                                                                           |
| Power output:           | P-Con (grey), mounting version                                                                                                                                         |
| Lamp type:              | LED lamp                                                                                                                                                               |
| LED type:               | 12 x 8 W high-power 4in1 RGBW (homogenous color mix)                                                                                                                   |
| Flash rate:             | 1 - 20 Hz                                                                                                                                                              |
| DMX channels:           | 3; 4; 5; 6; 9                                                                                                                                                          |
| DMX input:              | 1 x 3-pin XLR (M) mounting version                                                                                                                                     |
| DMX output:             | 1 x 3-pin XLR (F) mounting version                                                                                                                                     |
| Cooling:                | Passive convection cooling                                                                                                                                             |
| Control:                | DMX; IR remote control; stand-alone; QuickDMX via USB (optional); sound to light via microphone; master/slave function                                                 |
| Fixtures available for: | LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; Light´ J; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Beam angle:             | 16°                                                                                                                                                                    |
| Beam angle (1/2 peak):  | 16°                                                                                                                                                                    |
| Beam angle (1/10 peak): | 35°                                                                                                                                                                    |
| Color temperature:      | 6500K                                                                                                                                                                  |
| Housing color:          | Black matte                                                                                                                                                            |
| Attachment system:      | Double bracket                                                                                                                                                         |
| Display type:           | Monochrome 4 digit 7-segment LED display                                                                                                                               |
| Material:               | Aluminum casting; metal                                                                                                                                                |
| Dimensions:             | Width: 28.5 cm<br>Depth: 10.5 cm<br>Height: 29.5 cm                                                                                                                    |
| Weight:                 | 3.50 kg                                                                                                                                                                |
| Noise classification:   | Class 0 (no noise at all)                                                                                                                                              |
| Photobiological safety: | Risk Group 0                                                                                                                                                           |

|                          |                                                         |
|--------------------------|---------------------------------------------------------|
| Cable construction:      | 3 x 1.0 mm² H05VV-F                                     |
| Cable length:            | Approx. 1.2 m                                           |
| Diameter mounting holes: | 3 x Ø11mm                                               |
| Material:                | Metal, 3 mm                                             |
| Battery:                 | 1 x button cell 3.0 V CR2025 lithium manganese built-in |

**ROADINGER Flightcase 4x LED 4/7C-12 Silent Slim Spot**

|                        |                                               |
|------------------------|-----------------------------------------------|
| Maximum load:          | 50 kg                                         |
| Case handle:           | 2 pc/pcs                                      |
| Stop hinge:            | 2 pc/pcs                                      |
| Lock:                  | Butterfly lock: 2 pc/pcs                      |
| Use of brands:         | Branded hardware                              |
| Material:              | Birch multiplex                               |
| Color:                 | Dark brown, laminated                         |
| Device compartment:    | 29.5 cm x 13.5 cm x 27 cm                     |
| Accessory compartment: | 63 cm x 10.5 cm x 27 cm                       |
| Inside dimensions:     | 63 cm x 42 cm x 27 cm                         |
| Dimensions:            | Width: 67 cm<br>Depth: 46 cm<br>Height: 37 cm |
| Weight:                | 11.00 kg                                      |

**Scope of delivery:**

- 1 x spotlight
- 1 x power cord
- 1 x remote control
- 1 x user manual