

EUROLITE Set PAR-16 Spot sil + GU-10 230V COB 5W LED 1800-3000K dim2warm

PAR-16 housing with GU-10 socket including LED lamp with modern dim-to-warm-feature

GTIN: 4026397361582



Features:

- Mini-spot for GU-10 lamp
- Control via plug and play
- For PAR 16
- For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- <p>OMNILUX GU-10 230V COB 5W LED 1800-3000K dim2warm
- **LED lamp with modern dim-to-warm feature**
- Dimming behavior comparable with incandescent and halogen lamps (dim-to-warm)
- Changes the light color from 3000 K (warm white) to 1800 K (extra warm white) when dimming
- Creates particularly cosy atmospheres
- Easy lamp replacement
- Energy-saving
- Dimmable
- Easy installation
- With a beam angle of 24°
- Variable color temperature 1800 K - 3000 K
- Very high color rendering index (CRI)

Logistic

EAN / GTIN: 4026397361582

Weight: 0,50 kg

Length: 0.17 m

Width: 0.10 m

Heigh: 0.10 m

Technical specifications:

Weight: 0.32 kg

Energy efficiency class (A - G):	F
----------------------------------	---

EUROLITE PAR-16 Spot GU-10 silver

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 75 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 0.75 mm² H05SS-F
Cable length:	Approx. 0.4 m
Base:	GU10
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-16
Housing color:	Silver
Material:	Aluminum, 1 mm
Slot for spot length:	8 cm x 8 cm
Dimensions:	Length: 17 cm Width: 11 cm Height: 13 cm
Weight:	0.28 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Shape:	Octagonal
Material:	Aluminum
Dimensions:	Length: 7.7 cm Width: 7.7 cm Diameter: Ø 5.3 cm
Weight:	0.01 kg

OMNILUX GU-10 230V COB 5W LED 1800-3000K dim2warm

Operating voltage:	230
Nominal wattage:	5 W
Base:	GU10
Lamp type:	LED lamp; reflector lamp
Lamp specification:	Dimmable
Measurand (Pst LM):	0.0
Setup:	Easy installation
Beam angle:	24°
Beam angle (1/2 peak):	24°
Beam angle (1/10 peak):	60°
Color of light:	White

Color temperature:	1800K - 3000K adjustable
Color rendering index (CRI):	90 Ra
Luminous flux maintenance:	13
MacAdam Color consistency:	3
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Lamp life:	15000 h
Luminous flux:	400 lm
Luminous flux maintenance:	0.97
Wavelength:	640 nm
Material:	Aluminum casting
Dimensions:	Width: 5 cm Depth: 5 cm Height: 5 cm
Weight:	0.04 kg
Energy efficiency class (A - G):	F
EPREL-Nr:	960770

Scope of delivery:

- 1 x spotlight
- 1 x filter frame
- 1 x user manual