

EUROLITE Set 4x PAR-16 Spot bk dim2warm + EDX-4 DMX RDM LED Dimmer Pack

GTIN: 4026397366587



Features:

EUROLITE PAR-16 Spot GU-10 black

PAR-16 housing with GU10 socket (with plug + cable)

- Mini-spot for GU-10 lamp
- Color-filters attachable
- Control via plug and play
- For PAR 16
- For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation

OMNILUX GU-10 230V COB 5W LED 1800-3000K dim2warm

LED lamp with modern dim-to-warm feature

- Dimming behavior comparable with incandescent and halogen lamps (dim-to-warm)
- Changes the light color from 3000 K (warm white) to 1800 K (extra warm white) when dimming
- Creates particularly cosy atmospheres
- Easy lamp replacement
- Energy-saving
- Dimmable
- Easy installation
- With a beam angle of 24°

Logistic

EAN / GTIN: 4026397366587

Weight: 5,00 kg

Length: 0.61 m

Width: 0.31 m

Height: 0.42 m

- Variable color temperature 1800 K - 3000 K
- Very high color rendering index (CRI)

EUROLITE EDX-4 DMX RDM LED Dimmer Pack

4-channel dimmer for LED lights with 230 V operation

- Trailing edge dimmer with 4 channels
- Max. channel load 200 watts
- Independent DMX addressing per channel possible
- Dimmer or switch operation
- 4 channel faders for control on the device
- Note: Only suitable for LED - not for conventional light bulbs
- 16 integrated show programs
- Can be operated in 1; 4; 6 CH mode
- Control via RDM; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- With rigging points
- LCD display
- For application areas such as: Trade fair and shop fitting; theater; rental; video and photography; restaurants, bars and hotels
- Silent operation
- Application possibility: Wall mounting

Technical specifications:

Weight:	3.81 kg
---------	---------

Energy efficiency class (A - G):	F
----------------------------------	---

EUROLITE PAR-16 Spot GU-10 black

Power supply:	230 V AC, 50 Hz
---------------	-----------------

Power consumption:	Max. 75 W
--------------------	-----------

Protection class:	Protection class I
-------------------	--------------------

Power connection:	Fixed power supply cord with safety plug
-------------------	--

Cable construction:	3 x 0.75 mm² H05SS-F
---------------------	----------------------

Cable length:	Approx. 0.4 m
---------------	---------------

Base:	GU10
-------	------

Lamp type:	Selectable
------------	------------

Color generation:	Via color filter frame
-------------------	------------------------

Control:	Plug and play
----------	---------------

Construction:	PAR-16
---------------	--------

Housing color:	Black
----------------	-------

Material:	Aluminum, 1 mm
-----------	----------------

Slot for spot length:	7.8 cm x 7.8 cm
-----------------------	-----------------

Dimensions:	Length: 17 cm
	Width: 11 cm
	Height: 13 cm

Weight:	0.28 kg
---------	---------

Noise classification:	Class 0 (no noise at all)
-----------------------	---------------------------

Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Shape:	Octagonal
Material:	Aluminum, 1 mm
Dimensions:	Width: 7.7 cm Height: 7.7 cm Diameter: Ø 5.2 cm
Weight:	0.01 kg

OMNILUX GU-10 230V COB 5W LED 1800-3000K dim2warm

Operating voltage:	230
Nominal wattage:	5 W
Base:	GU10
Lamp type:	LED lamp; reflector lamp
Lamp specification:	Dimmable
Measurand (Pst LM):	0.0
Setup:	Easy installation
Beam angle:	24°
Beam angle (1/2 peak):	24°
Beam angle (1/10 peak):	60°
Color of light:	White
Color temperature:	1800K - 3000K adjustable
Color rendering index (CRI):	90 Ra
Luminous flux maintenance:	13
MacAdam Color consistency:	3
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Lamp life:	15000 h
Luminous flux:	400 lm
Luminous flux maintenance:	0.97
Wavelength:	640 nm
Material:	Aluminum casting
Dimensions:	Width: 5 cm Depth: 5 cm Height: 5 cm
Weight:	0.04 kg
Energy efficiency class (A - G):	F
EPREL-Nr:	960770

EUROLITE EDX-4 DMX RDM LED Dimmer Pack

Power supply:	230 V AC, 50 Hz
Output power:	Max. 200 W Max. 800 W

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	4 x safety contact (F), hinged lid mounting version fused 1 x P-Con (grey), mounting version Bypass
Fuse:	5 x 20 mm, F 6 A fuse replaceable
Power output fuse per channel:	5 x 20 mm, T 1 A fuse replaceable
DMX channels:	1; 4; 6
DMX input:	3-pin XLR (M)
DMX output:	3-pin XLR (F)
Control:	RDM; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Control channels:	4
Flying points:	2 x M10 thread
Display type:	LCD display
Status LED:	Channel level meter
Color:	Black
Dimensions:	Width: 21 cm Depth: 29 cm Height: 9 cm
Weight:	2.53 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:

4 x EUROLITE PAR-16 Spot GU-10 black

1 x spotlight
1 x filter frame
1 x user manual

1 x EUROLITE EDX-4 DMX RDM LED Dimmer Pack

1 x device
1 x user manual
1 x power cord