

EUROLITE Set LED KLS-3002 + Controller + STV-40S-WOT Steel stand

KLS incl. DMX lighting desk, DMX transmitter, miniature DMX transceiver and steel stand

Art. No.: 20000718

GTIN: 4026397304299



The article is no longer in our assortment.

Features:

- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- Mounting points and power outlets for additional fixtures
- 7 LEDs 10 W SMD 9090 6in1 RGBWA/UV (homogenous color mix)
 spots controlled separately
- Dimmer electronic; color blend stepless; color selection; program selection
- UV effect
- 20 integrated show programs
- Direct color selection for 21 preset colors
- Can be operated in 2; 4; 6; 10; 24; 28 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- With a beam angle of 19°
- TV spigot
- With omega bracket
- Monochrome 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; rental
- Silent operation
- Application possibility: Suspended; on stand
- <p>EUROLITE DMX LED Color Chief Controller
- DMX lighting desk with innovative control concept for LED spotlights**
- Easy control of LED spotlights with up to 6 colors, light bars as well as simple lighting effects
- For 8 devices or device groups, each with up to 4 segments

Logistic

EAN / GTIN: 4026397304299

Weight: 25,00 kg

Length: 1.35 m

Width: 0.21 m

Height: 0.58 m

Bulky product

- Quick and easy programming
- Additional fixtures can be configured manually
- 8 color effects directly selectable
- 3 additional channels available per fixture (e.g. for rotations)
- Color wheel selection and simulation
- 24 memory spaces for scenes and chases
- Several chases and scenes can be run simultaneously
- USB port for storing program data
- Sound control via audio signal or TAP button
- Master dimming, fade time and run time easily adjustable
- Can transmit up to 240 DMX channels
- (19") 48.3 cm rack installation 3 U
- Programmable 24 scenes/chases distributed over 1 page/s
- Control via DMX; sound to light via RCA (F) mounting version; sound to light via microphone
- Firmware can be updated
- Desktop console housing
- For application areas such as: Clubs/dancing school; party room; Trade fair and shop fitting; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation

<p>EUROLITE QuickDMX Wireless Transmitter

Compact wireless DMX transmitter 2.4 GHz

- User-friendly 3-pin XLR adapter (male) with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- 1 to 512 QuickDMX receivers can be controlled by each transmitter
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Can transmit up to 512 DMX channels
- Control via QuickDMX; DMX; plug and play
- Operating range up to 400m
- Up to 6 transmitters can be operated in parallel without interference

<p>EUROLITE QuickDMX USB Wireless Transmitter/Receiver

Wireless miniature DMX transceiver 2.4 GHz, phantom powered

- User-friendly USB plug with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Requires 5 V phantom power for operation
- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Control via DMX; QuickDMX; plug and play
- Operating range up to 400m with line-of-sight
- Up to 6 transmitters can be operated in parallel without interference

<p>EUROLITE STV-40S-WOT Steel Stand

Steel lighting stand without crossbar, max. load 18 kg, max. height 340 cm

- Stable lighting stand for mobile use
- The telescopic tube is additionally fixed with a safety pin
- Complies with DIN 15560-27 and DIN EN ISO 12100-2
- Adjustable height
- TV spigot

Technical specifications:

Weight: 21.75 kg

EUROLITE LED KLS-3002 Next Compact Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	225 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	3 m
Power output:	2 x IEC connector (F) mounting version fused 1 x P-Con (grey), mounting version Bypass
Fuse:	5 x 20 mm, T 2.5 A fuse replaceable
Power output fuse per channel:	5 x 20 mm, T 5 A fuse replaceable
Lamp type:	LED lamp
LED type:	7 x 10 W SMD 9090 6in1 RGBWA/UV (homogenous color mix)
DMX channels:	2; 4; 6; 10; 24; 28
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	EASY SHOW 1; Light´J; LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Beam angle:	19°
Beam angle (1/2 peak):	19°
Beam angle (1/10 peak):	35°
Housing color:	Black
Attachment system:	TV spigot Ø 28mm Omega bracket
Display type:	Monochrome 4 digit 7-segment LED display
Dimensions:	Width: 128 cm Depth: 8 cm Height: 29 cm
Weight:	11.14 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

EUROLITE DMX LED Color Chief Controller

Power supply:	100-240 V AC, 50/60 Hz 9V DC 800 mA
Power consumption:	7.2 W
Protection class:	Protection class III

Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Programmable 24 scenes/chases distributed over 1 page/s
DMX channels:	Output 240
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; sound to light via RCA (F) mounting version; sound to light via microphone
Housing color:	Black
Available storage media:	USB devices (FAT 32)
USB port:	Type A
Color:	Black
PC connect:	, firmware can be updated
Housing design:	(19") 48.3 cm rack installation 3 U Desktop console housing
Dimensions:	Width: 48.3 cm Depth: 13.35 cm Height: 8.5 cm
Weight:	2.25 kg
Noise classification:	Class 0 (no noise at all)

EUROLITE QuickDMX Wireless Transmitter

Power supply:	100-240 V AC, 50/60 Hz 5V DC 1000 mA
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord for USB A mains connection (provided)
DMX channels:	Output 512
DMX input:	1 x 3-pin XLR (M)
Control:	QuickDMX; DMX; plug and play
Range:	Range up to 400m
Carrier frequency:	2.4 GHz
Parallel mode:	Max. 6 transmitter
RF power output:	19 dBm
Modulation:	GFSK
Color:	Silver
Dimensions:	Length: 21.2 cm Diameter: Ø 1.8 cm
Weight:	0.15 kg

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

Power supply:	5V DC
Protection class:	Protection class III
Power connection:	Mains input via USB A (M) connectable version

DMX channels:	Input 512 Output 512
DMX output:	1 x USB, type A
Control:	DMX; QuickDMX; plug and play
Range:	Range up to 400m with line-of-sight
Carrier frequency:	2.4 GHz
Parallel mode:	Max. 6 transmitter
RF power output:	19 dBm
Modulation:	GFSK
Housing color:	Black
USB port:	Type A
Material:	Plastic
Color:	Black
Dimensions:	Width: 8.6 cm Depth: 4 cm Height: 1.1 cm
Weight:	0.01 kg

EUROLITE STV-40S-WOT Steel Stand

Maximum carrying capacity:	18 kg
Standard:	DIN 15560-27, DIN EN ISO 12100-2
Height:	Maximum: 340 cm above 2 sections Minimum: 150 cm
Attachment system:	TV spigot Ø 28mm
Type (general stands):	Light stand/manual
Color:	Black
Transport dimensions:	159 cm x 18 cm x 15 cm
Base area:	Ø 120 cm
Weight:	8.20 kg

Scope of delivery:

1 x EUROLITE LED KLS-3002 Next Compact Light Set

1 x device
 1 x user manual
 1 x declaration of conformity
 1 x power cord
 1 x remote control
 1 x bag
 2 x omega bracket
 4 x knurled screw
 4 x washer
 1 x battery
 1 x terminating plug (power)

1 x EUROLITE DMX LED Color Chief Controller

1 x controller
 1 x user manual
 1 x external mains adapter

1 x EUROLITE QuickDMX Wireless Transmitter

1 x device
1 x user manual
1 x declaration of conformity
1 x external mains adapter
1 x USB cable

1 x EUROLITE QuickDMX USB Wireless Transmitter/Receiver

1 x device
1 x user manual
1 x declaration of conformity

1 x EUROLITE STV-40S-WOT Steel Stand

1 x stand
1 x user manual