

EUROLITE Set LED KLS-902 + STV-40S-WOT Steel Stand

Bar with 4 powerful RGB/WW spots, QuickDMX, remote control and bag incl. steel stand

Art. No.: 20000721

GTIN: 4026397340853



The article is no longer in our assortment.

Features:

- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- Mounting points and power outlets for additional fixtures
- 5 LEDs 7 W SMD 9080 4in1 RGB/WW (homogenous color mix)
 spots controlled separately
- Color blend stepless; Dimmer electronic; program selection
- 20 integrated show programs
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; sound to light via microphone; IR remote control; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- With a beam angle of 16°
- TV spigot
- With omega bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Mobile use; stage; mobile djs / entertainer; small rental; rental
- Very quiet working noise
- Application possibility: Suspended; on stand
- Can be operated in 3; 4; 6; 8; 16; 20; 18 CH mode
- <p>EUROLITE STV-40S-WOT Steel Stand
- **Steel lighting stand without crossbar, max. load 18 kg, max. height 340 cm**
- Stable lighting stand for mobile use
- The telescopic tube is additionally fixed with a safety pin
- Complies with DIN 15560-27 and DIN EN ISO 12100-2
- Adjustable height
- TV spigot

Logistic

EAN / GTIN: 4026397340853

Weight: 20,50 kg

Length: 1.35 m

Width: 0.21 m

Height: 0.58 m

Bulky product

Technical specifications:

Weight:	18.00 kg
---------	----------

EUROLITE LED KLS-902 Next Compact Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	125 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	3 m
Power output:	2 x IEC connector (F) mounting version 1 x P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Power output fuse per channel:	5 x 20 mm, T 5 A fuse replaceable
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Lamp type:	LED lamp
LED type:	5 x 7 W SMD 9080 4in1 RGB/WW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 16; 20; 18
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; sound to light via microphone; IR remote control; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; Light J; EASY SHOW 3; Colorchief
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	32°
Housing color:	Black
Attachment system:	TV spigot Ø 28mm Omega bracket
Dimensions:	Width: 108 cm Depth: 6 cm Height: 28 cm
Weight:	9.80 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)

EUROLITE STV-40S-WOT Steel Stand

Maximum carrying capacity:	18 kg
Standard:	DIN 15560-27, DIN EN ISO 12100-2
Height:	Maximum: 340 cm above 2 sections Minimum: 150 cm
Attachment system:	TV spigot Ø 28mm
Type (general stands):	Light stand/manual
Color:	Black
Transport dimensions:	159 cm x 18 cm x 15 cm
Base area:	Ø 120 cm
Weight:	8.20 kg

Scope of delivery:**1 x EUROLITE LED KLS-902 Next Compact Light Set**

1 x light effect
1 x user manual
1 x power cord
1 x remote control
1 x battery
2 x omega bracket
1 x declaration of conformity
4 x knurled screw
1 x bag

1 x EUROLITE STV-40S-WOT Steel Stand

1 x stand
1 x user manual