

FUTURELIGHT Set 4x EYE-7 HCL Zoom + Case

4x PRO washlight with 6in1 COB LEDs and motorized zoom including PRO flightcase

Art. No.: 20000724

GTIN: 4026397471878



The article is no longer in our assortment.

Features:

- Equipped with 7 x 17 W 6in1 LED in R/G/B/Amber/Lime/Cyan
- Variable PWM frequency (pulse-width modulation)
- Optional W-DMX receiver for wireless DMX Control
- Compact design
- 2 different LED segments, which can be controlled individually via DMX
- Exact positioning via 16-bit PAN/TILT movement resolution
- 16-bit resolution for high-resolution dimming
- Motorized zoom with 2-36° beam angle
- Color presets
- Variable color temperature
- Built-in programs
- Stepless color blend
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- ESDC function (Easy Service Data Check) with battery-buffered control board for operation time readouts etc. (the Li-Ion battery 3.7V, AAA, 10440 is not included)
- Control panel with LC display for easy configuration
- Stand-alone, master/slave and DMX mode
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- 7 LEDs 17 W high-power 6in1 RGBALC (homogenous color mix)
- PAN angle switchable between 540° and 630°

Logistic

EAN / GTIN: 4026397471878

Weight: 58,00 kg

Length: 1.20 m

Width: 80.00 m

Height: 0.60 m

Bulky product

- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven
- Strobe effect
- Can be operated in 16; 19; 20; 33 CH mode
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; RDM; W-DMX by wireless solution upgradeable; master/slave function; sound to light via microphone
- Flicker-free
- With a beam angle of 2° - 36°
- Built with NEUTRIK connector
- <p>ROADINGER Flightcase 4x EYE-7 RGBW Zoom

Trunk case with castors

)

- With 4 device compartments
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes
- Branded hardware
- Made in Germany
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	49.40 kg
---------	----------

FUTURELIGHT EYE-7 HCL Zoom LED Moving Head Wash

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	130 W
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug
Power output:	1 x PowerCON (grey), mounting version
Fuse:	5 x 20 mm, T 3.15 A fuse replaceable
Lamp type:	LED lamp
LED type:	7 x 17 W high-power 6in1 RGBALC (homogenous color mix)
Max. TILT movement:	270° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540°, 630° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	1 - 18 Hz
Equipment:	Zoom motor driven
DMX channels:	16; 19; 20; 33
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan

Control:	Stand-alone; DMX; RDM; W-DMX by wireless solution upgradeable; master/slave function; sound to light via microphone
Fixtures available for:	LED PC-Control 512; Light Captain; Light J
Projection:	Flicker-free
Beam angle:	2° - 36°
Beam angle (1/2 peak):	2 - 15°
Beam angle (1/10 peak):	7 - 36°
Illuminance in Lux (lx):	Narrow red (R) 1m: 7036 lx, 3m: 1003 lx, 6m: 248 lx Narrow green (G) 1m: 14473 lx, 3m: 2193 lx, 6m: 548 lx Narrow blue (B) 1m: 2461 lx, 3m: 478 lx, 6m: 122 lx Narrow amber (A) 1m: 27460 lx, 3m: 4256 lx, 6m: 1066 lx Narrow lime 1m: 44659 lx, 3m: 6773 lx, 6m: 1705 lx Narrow cyan 1m: 6274 lx, 3m: 1011 lx, 6m: 251 lx Narrow all 3m: 14976 lx, 6m: 3744 lx Wide red (R) 1m: 787 lx, 3m: 95 lx, 6m: 25 lx Wide green (G) 1m: 1716 lx, 3m: 215 lx, 6m: 58 lx Wide blue (B) 1m: 392 lx, 3m: 51 lx, 6m: 14 lx Wide amber (A) 1m: 3202 lx, 3m: 388 lx, 6m: 104 lx Wide lime 1m: 4793 lx, 3m: 594 lx, 6m: 160 lx Wide cyan 1m: 839 lx, 3m: 103 lx, 6m: 28 lx Wide all 1m: 11196 lx, 3m: 1365 lx, 6m: 362 lx
Housing color:	Black
Use of brands:	Built with NEUTRIK connector
Dimensions:	Width: 24.9 cm Depth: 17.9 cm Height: 34.7 cm
Weight:	7.30 kg
Noise classification:	Class 3 (clearly perceptible sounds)

ROADINGER Flightcase 4x EYE-7 RGBW Zoom

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Middle compartment:	10.5 cm x 38 cm
Inside dimensions:	72.5 cm x 48 cm x 47 cm
Device compartment:	25 cm x 38 cm

Dimensions:

Width: 75 cm

Depth: 49.5 cm

Height: 62 cm

Weight:

20.20 kg

Scope of delivery:

1 x moving light
1 x power cord
1 x user manual
1 x declaration of conformity
1 x mounting bracket
1 x XLR cable