

## EUROLITE Set 2x LED TMH-S90 + Case

2x Led moving head spot including flightcase with wheels

Art. No.: 20000743

GTIN: 4026397681802



### Features:

- Positioning within
- <p>EUROLITE LED TMH-S90 Moving Head Spot
- **LED moving head spot with color wheel, static and rotating gobo wheel, prism and focus**
- Rotating 3-facet prism with variable speed
- 1 LED 90 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN, 200° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Prism 3-fold; gobo wheel with rotating gobos; gobo wheel with static gobos; focus motor-driven; color wheel
- Dimmer electronic
- Color wheel with 7 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 7 gobos and open<BR>shake effect
- Gobo wheel with rotating gobos, 5 gobos, 1 multi color gobo and open<BR>shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- Integrated show programs
- Can be operated in 15 CH mode
- The device is cooled by cooling fan
- Control via DMX; sound to light via microphone; stand-alone; master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
- Flicker-free
- With a beam angle of 12°
- LCD display

### Logistic

EAN / GTIN: 4026397681802

Weight: 23,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.37 m

Bulky product

- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended
- <p>ROADINGER Flightcase 2x TMH-S90/H90/B90

#### **Trunk case with castors**

- For optimal security
- With 2 device compartments
- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function; 2 high-quality butterfly locks
- Closes with a
- Castors

## **Technical specifications:**

|         |          |
|---------|----------|
| Weight: | 25.55 kg |
|---------|----------|

### **EUROLITE LED TMH-S90 Moving Head Spot**

|                     |                                                                                                                                                                                                                                                                            |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:       | 100-240 V AC, 50/60 Hz                                                                                                                                                                                                                                                     |
| Power consumption:  | 140 W                                                                                                                                                                                                                                                                      |
| Protection class:   | Protection class I                                                                                                                                                                                                                                                         |
| Power connection:   | Mains input via P-Con (blue), mounting version power supply cord with safety plug                                                                                                                                                                                          |
| Power output:       | P-Con (grey), mounting version                                                                                                                                                                                                                                             |
| Fuse:               | 5 x 20 mm, T 2 A                                                                                                                                                                                                                                                           |
| Lamp type:          | LED lamp                                                                                                                                                                                                                                                                   |
| LED type:           | 1 x 90 W COB (chip-on-board) cold white (CW)                                                                                                                                                                                                                               |
| Max. TILT movement: | 200° exact positioning (16 bit resolution) auto position correction (feedback)                                                                                                                                                                                             |
| Max. PAN movement:  | 540° exact positioning (16 bit resolution) auto position correction (feedback)                                                                                                                                                                                             |
| Flash rate:         | 1.5 - 15 Hz                                                                                                                                                                                                                                                                |
| Equipment:          | Prism 3-fold; gobo wheel with rotating gobos; gobo wheel with static gobos; focus motor-driven; color wheel                                                                                                                                                                |
| Color generation:   | Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions                                                                                                                                              |
| Gobos:              | Gobo wheel with static gobos, 7 gobos and open Shake effect<br>Gobo wheel with rotating gobos, 5 gobos, 1 multi color gobo and open<br>Outside diameter 21.8mm<br>Image diameter 16mm<br>Shake effect<br>Gobos changeable<br>Slot-in gobo system for easy gobo replacement |
| DMX channels:       | 15                                                                                                                                                                                                                                                                         |

|                          |                                                                                                                                                                                           |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DMX input:               | 3-pin XLR (M) mounting version                                                                                                                                                            |
| DMX output:              | 3-pin XLR (F) mounting version                                                                                                                                                            |
| Cooling:                 | Cooling fan                                                                                                                                                                               |
| Control:                 | DMX; sound to light via microphone; stand-alone; master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional) |
| Fixtures available for:  | EASY SHOW 1; Light Captain; EASY SHOW 3                                                                                                                                                   |
| Projection:              | Flicker-free                                                                                                                                                                              |
| PWM frequency:           | 15600 Hz                                                                                                                                                                                  |
| Beam angle:              | 12°                                                                                                                                                                                       |
| Beam angle (1/2 peak):   | 12°                                                                                                                                                                                       |
| Illuminance in Lux (lx): | Cold white (CW) 1m: 52772 lx, 3m: 6198 lx, 6m: 1543 lx                                                                                                                                    |
| Housing color:           | Black                                                                                                                                                                                     |
| Display type:            | LCD display                                                                                                                                                                               |
| Dimensions:              | Width: 25.0 cm<br>Depth: 20.5 cm<br>Height: 35.0 cm                                                                                                                                       |
| Weight:                  | 6.20 kg                                                                                                                                                                                   |
| Noise classification:    | Class 3 (clearly perceptible sounds)                                                                                                                                                      |
| Photobiological safety:  | Risk Group 0                                                                                                                                                                              |

#### ROADINGER Flightcase 2x TMH-S90/H90/B90

|                          |                                                                              |
|--------------------------|------------------------------------------------------------------------------|
| Maximum load:            | 50 kg                                                                        |
| Aluminum profile frames: | 30 mm                                                                        |
| Case handle:             | 2 pc/pcs                                                                     |
| Stop hinge:              | 2 pc/pcs                                                                     |
| Lock:                    | Butterfly lock: 2 pc/pcs with shut-off function;<br>butterfly lock: 2 pc/pcs |
| Transport aid:           | Castors                                                                      |
| Material:                | Plywood multi-layer glued, 7 mm                                              |
| Color:                   | Black, laminated                                                             |
| Device compartment:      | 20 cm x 26 cm x 37 cm                                                        |
| Accessory compartment:   | 9.5 cm x 26 cm x 37 cm                                                       |
| Dimensions:              | Width: 57 cm<br>Depth: 31 cm<br>Height: 54 cm                                |
| Weight:                  | 13.15 kg                                                                     |

#### Scope of delivery:

1 x moving light  
 1 x user manual  
 1 x power cord  
 1 x omega bracket  
 1 x safety eyelet