

EUROLITE Set LED SL-350 DMX + STV-250

Follow spot with cold white 300 W LED including follow stand

Art. No.: 20000749

GTIN: 4026397682434



List price: 2081.31 €

incl. 19% VAT.

Features:

- Manual control via control panel with buttons and faders
- 1 LED 300 W COB (chip-on-board) cold white (CW)
- Focus manual; iris stepless
- Dimmer electronic
- Strobe effect
- Color wheel with 5 dichroic filters plus open
- Can be operated in 6 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; DMX
- With a beam angle of 10°
- Direct color temperature selection for 3 preset values
- With mounting bracket
- 4 digit 7-segment LED display
- Suitable for a range of use from 10 to 30 meters
- For application areas such as: Stage; wedding/gala/events; theater; rental
- Application possibility: Suspended; on stand
- <p>EUROLITE STV-250 Follow Spot Stand, black
- **PRO follow stand for mobile lighting systems**
- Heavy-duty stainless steel version for extra stability and safety
- Tripod legs made of stainless steel
- Tripod legs with optional slant for uneven surfaces
- Easy handling
- Safety ring for height adjustment
- Extra-big, rubberized star knob screw
- Adjustable height
- With Multi-angle ball head bracket with stainless steel rod

Logistic

EAN / GTIN: 4026397682434

Weight: 22,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Technical specifications:

Weight:	19.00 kg
---------	----------

EUROLITE LED SL-350 DMX Search Light

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	440 W
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 5 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 300 W COB (chip-on-board) cold white (CW)
Flash rate:	0 - 20 Hz
Equipment:	Focus manual; iris stepless
Color generation:	Color wheel with 5 dichroic filters plus open
DMX channels:	6
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX
Fixtures available for:	Light´ J; LED PC-Control 512; Light Captain
Beam angle:	10°
Beam angle (1/2 peak):	10°
Housing color:	Black matte
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum casting; metal
Range of use:	- 30m
Dimensions:	Length: 60 cm Width: 27.5 cm Height: 30 cm
Weight:	10.55 kg
Noise classification:	Class 2 (slight noise)
Cable construction:	3 x 1.5 mm² H05VV-F
Cable length:	Approx. 1.4 m
Cable length:	Approx. 2 m
Diameter mounting holes:	3 x Ø13mm; 2 x Ø15mm
Material:	Metal, 4 mm
Dimensions:	Width: 6 cm

EUROLITE STV-250 Follow Spot Stand, black

Maximum carrying capacity:	50 kg
Height:	Maximum: 170 cm Minimum: 95 cm
Attachment system:	M10 thread Multi-angle ball head bracket with stainless steel rod
Type (general stands):	Light stand/manual
Material:	Aluminum; stainless steel
Color:	Black
Base area:	Ø 1.12 cm
Transport dimensions:	13 cm x 14 cm x 105 cm
Weight:	8.45 kg

Scope of delivery:**1 x EUROLITE LED SL-350 DMX Search Light**

1 x spotlight
1 x user manual
1 x power cord
1 x XLR cable
1 x mounting bracket
1 x hex key

1 x EUROLITE STV-250 Follow Spot Stand, black

1 x stand
1 x user manual