

OMNITRONIC Set MOLLY-12A Subwoofer active + 4x MOLLY-6 Top 8 ohms, black

Active 12" subwoofer with DSP and Bluetooth incl. 4x 6.5" satellite speakers with bracket

Art. no. 00000757

GTIN: 4026397684384



List price: 1046.01 €

incl. 19% VAT.

Features:

- 12" bassreflex subwoofer with DSP and 700 watts RMS power
- Flexibly extendable with MOLLY-6 satellites for 2.1 and 4.1 configurations
- DSP-controlled class D amplifier (500 W + 2 x 100 W)
- Separate volume control for subwoofer and satellites
- Stereo/mono selection
- Digital signal processor
- DSP presets: FLAT; DJ; LIVE; VOICE
- The device is cooled by temperature-controlled fan
- Control via Bluetooth
- Operating range up to 10m
- Black metal grille with acoustic foam
- 2 Rugged carrying handles
- For application areas such as: Mobile djs / entertainer; Trade fair and shop fitting; installation; home entertainment; restaurants, bars and hotels; product presentations and lectures
- <p>OMNITRONIC MOLLY-6 Top black 2x
- **6.5" satellite speakers with bracket**
- 8-ohm speaker pair with 6.5" woofer and 1" tweeter
- For use with MOLLY-12A subwoofers for 2.1 and 4.1 configurations
- Optional stand adaptor required for stand mounting
- Extension U-bracket and cable available for connecting 2 satellite speakers
- With mounting bracket
- With rigging points
- Black metal grille with acoustic foam
- 2 pieces per set
- For application areas such as: Mobile djs / entertainer; Trade fair and shop fitting; installation; home entertainment; restaurants, bars and hotels; product presentations and lectures

Logistic

EAN / GTIN: 4026397684384

Weight: 41,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.50 m

Bulky product

Technical specifications:

Weight:	40.65 kg
---------	----------

OMNITRONIC MOLLY-12A Subwoofer active black

Power supply:	230 V AC, 50 Hz
Power consumption:	1000 W
Protection class:	Protection class I
Output power:	1 x 500 W RMS 2 x 100 W RMS (8 ohms) 2 x 200 W RMS (4 ohms)
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 5 A fuse replaceable
Frequency range:	40 - 160 Hz
Sensitivity:	103 dB
Max. SPL:	128 dB
DSP:	Digital signal processor
DSP presets:	FLAT; DJ; LIVE; VOICE
Cooling:	Temperature-controlled fan
Control:	Bluetooth
Bluetooth device name:	Omnitronic
Range:	Range up to 10m
Attachment system:	Flange: M20 thread
Circuitry:	Class D
Control elements:	Phase reversal switch, level control per channel, power switch, connect
Controls:	Softstart; short-circuit; limiter; Overvoltage; overheat
Status LED:	Signal, power, limit, fault, DSP presets
Connections:	Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: line via 1 x 3.5 mm jack (stereo) mounting version Input: line via 1 x stereo RCA Output: line via 2 x 3-pin XLR Output: top via 2 x speaker built-in socket (F)
Input channels:	1 x stereo via combination socket or RCA or Bluetooth, channel control via rotary dial
Speaker:	1 x woofer 12" Basket material: steel Conematerial: cardboard/paper Voice coil lows 3"
Type of speaker:	Subwoofer

Type of construction:	Vented
Carrying handle:	2 pc/pcs
Material:	Birch multiplex
Color:	Black, textured coating, painted
Dimensions:	Width: 47 cm Depth: 57 cm Height: 40 cm
Weight:	22.85 kg
Cable length:	3 m

OMNITRONIC MOLLY-6 Top black 2x

Power:	Program: 260W Rated: 130W RMS
Frequency range:	150 - 20000 Hz
Sensitivity:	95 dB (1W/1m)
Max. SPL:	119 dB
Impedance:	8 ohms
Attachment system:	2x mounting bracket
Flying points:	2 x M8 thread
Connections:	1 x speaker built-in socket (F) 1 x screw plug-in terminal
Speaker:	1 x woofer 6.5" Basket material: steel Voice coil lows 1" 1 x tweeter 1"
Type of speaker:	On ceiling/on wall speaker; coaxial speaker
Material:	MDF (medium density fiberboard)
Color:	Black, textured coating, painted
Dimensions:	Width: 18.3 cm Depth: 21.4 cm Height: 23 cm
Weight:	8.90 kg

Scope of delivery:

1 x OMNITRONIC MOLLY-12A Subwoofer active black

1 x bass
1 x power cord
2 x speaker cable
1 x user manual
1 x declaration of conformity

2 x OMNITRONIC MOLLY-6 Top black 2x

2 x top
2 x mounting bracket
4 x knurled screw
2 x screw plug-in terminal