

EUROLITE Set LED PLL-360 3200K + Stand

Surface light with 360 warm white LEDs and DMX incl. lighting stand and adapter

Art. No.: 20000798

GTIN: 4026397687415



Features:

- Frost filter provides a soft, homogeneous light
 - 4 barn doors to avoid blinding the audience and for protection during transport
 - Slim, rugged metal housing
 - Dimmable
 - 360 LEDs 0.5 W SMD 2835 warm white (WW)
 - Dimmer electronic; Dimmer speed (step response) adjustable
 - Strobe effect
 - Can be operated in 3 CH mode
 - The device is cooled by passive convection cooling
 - Control via quick select potentiometer for brightness; DMX; master/slave function
 - Flicker-free
 - With a beam angle of 120°
 - Very high color rendering index (CRI)
 - With mounting bracket
 - LCD display
 - Rugged carrying handle
 - Mains input and output for power linking up to 8 units
 - Various versions available
 - For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography
 - Silent operation
 - Application possibility: Suspended; on stand
 - <p>EUROLITE LS-1 EU Steel Stand
- Lighting stand made in EU, without crossbeam, maximum load 30 kg, height 145-315 cm**
- Stable lighting stand for mobile use
 - Adjustable height

Logistic

EAN / GTIN: 4026397687415

Weight: 14,00 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

- Made in Europe
- <p>EUROLITE LS-1A1 Adapter for LS-1
Universal adapter for lighting stands LS-1 and LS-1T
- Universal adapter allowing to mount a single spotlight
- Made in Europe

Technical specifications:

Weight:	11.66 kg
---------	----------

EUROLITE LED PLL-360 3200K Panel

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	130 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Lamp type:	LED lamp
Lamp specification:	Dimmable
LED type:	360 x 0.5 W SMD 2835 warm white (WW)
DMX channels:	3
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Quick select potentiometer for brightness; DMX; master/slave function
Fixtures available for:	Light´J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	120°
Color temperature:	3200K
Color rendering index (CRI):	94 Ra
Illuminance in Lux (lx):	Warm white (WW) 3m: 403 lx, 6m: 118 lx
Luminous flux:	9367 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Carrying handle:	1 pc/pcs
Dimensions:	Width: 57 cm Depth: 12 cm Height: 31 cm
Weight:	6.10 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F

EPREL-Nr:	1056205
-----------	---------

EUROLITE LS-1 EU Steel Stand

Maximum carrying capacity:	30 kg
Height:	Maximum: 315 cm Minimum: 145 cm
Attachment system:	Tube: Ø 28mm
Type (general stands):	Light stand/manual
Material:	Steel/magnesium
Color:	Black
Transport dimensions:	120 cm x 16 cm x 14 cm
Base area:	Ø 108 cm
Weight:	5.30 kg

EUROLITE LS-1A1 Adapter for LS-1

Maximum carrying capacity:	30 kg
Attachment system:	Ø 29mm M8 thread
Type (general stands):	Accessory
Material:	Steel
Color:	Black, powder-coated
Dimensions:	Width: 11 cm Depth: 9 cm Height: 10 cm
Weight:	0.26 kg

Scope of delivery:

1 x EUROLITE LED PLL-360 3200K Panel

1 x spotlight
1 x user manual
1 x power cord

1 x EUROLITE LS-1 EU Steel Stand

1 x stand
1 x user manual