

EUROLITE Set 4x LED CBB-2 COB RGB Bar + Case

4x LED light effect bar with RGB color mixing including PRO flightcase

Art. No.: 20000809

GTIN: 4026397687965



List price: 950.81 €

incl. 19% VAT.

Features:

- 2 LEDs 30 W COB (chip-on-board) 3in1 RGB (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 18 preset colors
- Can be operated in 3; 4; 5; 6; 11 CH mode
- The device is cooled by cooling fan
- Control via IR remote control; sound to light via microphone; stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
- Flicker-free
- With a beam angle of 38°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; decoration; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand
- <p>ROADINGER Flightcase 4 x LED CBB-2 COB Bar
- **Trunk case, PRO version**
- For optimal security
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 20mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks

Logistic

EAN / GTIN: 4026397687965

Weight: 20,00 kg

Length: 1.20 m

Width: 0.41 m

Height: 0.30 m

Bulky product

- 2 high-quality butterfly locks
- Closes with a
- Branded hardware

Technical specifications:

Weight:	17.41 kg
---------	----------

EUROLITE LED CBB-2 COB RGB Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
Lamp type:	LED lamp
LED type:	2 x 30 W COB (chip-on-board) 3in1 RGB (homogenous color mix)
Flash rate:	0.5 - 24 Hz
DMX channels:	3; 4; 5; 6; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	IR remote control; sound to light via microphone; stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
PWM frequency:	2900 Hz
Beam angle:	38°
Beam angle (1/2 peak):	38°
Beam angle (1/10 peak):	70°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Metal
Dimensions:	Width: 15.5 cm Depth: 24 cm Height: 17.5 cm
Weight:	2.39 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	3 x Ø11mm; 4 x Ø7mm
Material:	Metal, 2 mm
Battery:	1 x button cell CR2025

ROADINGER Flightcase 4 x LED CBB-2 COB Bar

Maximum load:	50 kg
Aluminum profile frames:	20 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm, laminated; birch multiplex
Color:	Dark brown, laminated
Device compartment:	25 cm x 12 cm x 25 cm
Accessory compartment:	10 cm x 27 cm x 25 cm
Inside dimensions:	63.5 cm x 27 cm x 25 cm
Dimensions:	Width: 68 cm
	Depth: 31 cm
	Height: 29 cm
Weight:	7.85 kg

Scope of delivery:

1 x spotlight
1 x power cord
1 x remote control
1 x battery
1 x user manual