

EUROLITE Set 4x LED CBB-2 COB WW Bar + Case

4x LED light effect bar with WW COB Leds including PRO flightcase

Art. No.: 20000811

GTIN: 4026397687989



Features:

- 2 LEDs 35 W COB (chip-on-board) warm white (WW)
- Dimmer electronic
- Strobe effect
- Integrated show programs
- Can be operated in 2; 3; 5 CH mode
- The device is cooled by cooling fan
- Control via IR remote control; sound to light via microphone; DMX; stand-alone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 37°
- Very high color rendering index (CRI)
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; decoration; wedding/gala/events; restaurants, bars and hotels; Trade fair and shop fitting; video and photography
- Application possibility: Standing; suspended; on stand
- <p>ROADINGER Flightcase 4 x LED CBB-2 COB Bar
- **Trunk case, PRO version**
- For optimal security
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 20mm with rounded edges
- 2 hinged, chromium plated case handles

Logistic

EAN / GTIN: 4026397687989

Weight: 20,00 kg

Length: 1.20 m

Width: 0.41 m

Height: 0.30 m

Bulky product

- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- Branded hardware

Technical specifications:

Weight:	17.65 kg
---------	----------

EUROLITE LED CBB-2 COB WW Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
Lamp type:	LED lamp
LED type:	2 x 35 W COB (chip-on-board) warm white (WW)
Flash rate:	0 - 20 Hz
DMX channels:	2; 3; 5
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	IR remote control; sound to light via microphone; DMX; stand-alone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	LED PC-Control 512; Light Captain; Light´J; Colorchief
Projection:	Flicker-free
Beam angle:	37°
Beam angle (1/2 peak):	37°
Beam angle (1/10 peak):	70°
Color temperature:	2700K
Color rendering index (CRI):	91 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 15.5 cm Depth: 24 cm Height: 17.5 cm
Weight:	2.45 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Maximum load:	50 kg
Aluminum profile frames:	20 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm, laminated; birch multiplex
Color:	Dark brown, laminated
Device compartment:	25 cm x 12 cm x 25 cm
Accessory compartment:	10 cm x 27 cm x 25 cm
Inside dimensions:	63.5 cm x 27 cm x 25 cm
Dimensions:	Width: 68 cm Depth: 31 cm Height: 29 cm
Weight:	7.85 kg

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery