



Features:

EUROLITE LED KLS Laser Bar Next FX Light Set

Bar with powerful spots, UV strobe LEDs, laser (RG, 2M), QuickDMX port and carrying bag

- 2 laser diodes project hundreds of red and green laser beams
- 2 rotating derbies for mirror ball effects
- Compact lightweight
- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- When fog is used, this effect becomes especially attractive
- Dimmer electronic; color blend stepless; program selection
- 26 integrated show programs
- Can be operated in 6; 8; 11; 21; 25; 29 CH mode
- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone; IR remote control; QuickDMX via USB (optional); wireless footswitch (optional)
- TV spigot
- With mounting bracket
- 3 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Application possibility: On stand

laser

Logistic

EAN / GTIN: 4026397689075

Weight: 20,00 kg

Length: 1.36 m

Width: 0.34 m

Height: 0.06 m

Bulky product

- Laser
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 3 LEDs 4 W SMD 9080 4in1 RGB/WW (homogenous color mix)
4 spots controlled separately
- With a beam angle of 7° spot
- light effect**
- 4 LEDs 3 W SMD 8072 R/G/B/WW
 lighting effects controlled separately
- Multi beam effect; fan effect; flower effect
- bar**
- 4 LEDs 1.5 W SMD 8072 ultra violet (UV)
 LEDs controlled separately
- UV effect; strobe effect

OMNITRONIC M-4 Speaker-System Stand

Aluminum speaker stand, height adjustable 140-345 cm, maximum load 18 kg

- Durable aluminum version
- Tube diameter: Ø 35 mm
- Adjustable height

EUROLITE STV-3529 Adapter long

Massive adapter for 35 mm tube, 28 mm TV spigot, maximum load WLL 100 kg

- For stands with telescopic tube 35 mm
- Connection element for cross beam with 28 mm TV spigot
- With M6 and M8 fixation screw
- Heavy version for highest stability
- TV spigot

Technical specifications:

Weight:	15.30 kg
---------	----------

EUROLITE LED KLS Laser Bar Next FX Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	90 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	3 m
Power output:	1 x P-Con (grey), mounting version
Fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
DMX channels:	6; 8; 11; 21; 25; 29
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; sound to light via microphone; IR remote control; QuickDMX via USB (optional); wireless footswitch (optional)

Fixtures available for:	Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Housing color:	Black
Attachment system:	TV spigot Ø 28mm 2x mounting bracket
Display type:	3 digit 7-segment LED display
Dimensions:	Width: 111 cm Depth: 15 cm Height: 41 cm
Weight:	10.50 kg
Noise classification:	Class 2 (slight noise)
Battery:	Button cell 3.0 V CR2025 lithium manganese built-in
Laser class:	2M
Laser color:	R/G
Laser module:	Red (R) 100 mW 650nm Green (G) 30 mW 532nm
LED type:	4 x 3 W SMD 8072 R/G/B/WW
LED type:	3 x 4 W SMD 9080 4in1 RGB/WW (homogenous color mix)
Beam angle:	7° spot
Beam angle (1/2 peak):	Spot 7°
Beam angle (1/10 peak):	Spot 20°
LED type:	4 x 1.5 W SMD 8072 ultra violet (UV)
Flash rate:	0 - 30 Hz

OMNITRONIC M-4 Speaker-System Stand

Maximum carrying capacity:	18 kg
Tube diameter sector:	38 - 35 mm
Height:	Maximum: 345 cm Minimum: 140 cm Adjustable in 10 steps with locking pin
Attachment system:	Ø 35mm
Type (general stands):	Speaker stand/manual
Material:	Aluminum
Color:	Black
Transport dimensions:	140 cm x 13.5 cm
Weight:	3.30 kg

EUROLITE STV-3529 Adapter long

Maximum load BGV C1 (8-fold):	50 kg
Maximum load WLL (4-fold):	100 kg
Attachment system:	TV spigot Ø 28mm Ø 35mm
Type (general stands):	Accessory

Material:	Steel, 6 mm, powder-coated
Dimensions:	Width: 8.50 cm
	Depth: 5 cm
	Height: 19.50 cm
Weight:	1.50 kg

Scope of delivery:

1 x EUROLITE LED KLS Laser Bar Next FX Light Set

1 x device
1 x user manual
1 x power cord
1 x bag
1 x declaration of conformity
1 x remote control
2 x mounting bracket
2 x knurled screw
2 x washer
1 x terminating plug (power)

1 x OMNITRONIC M-4 Speaker-System Stand

1 x user manual

1 x EUROLITE STV-3529 Adapter long

1 x device
1 x user manual
2 x knurled screw