



The article is no longer in our assortment.

Features:

EUROLITE AKKU IP PAR 14 HCL QuickDMX

IP65 battery-powered spotlight with RGBWA+UV LEDs, QuickDMX, frost filter and IR remote control

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 26h depending on program used
- 14 LEDs 10 W 6in1 RGBWA/UV (homogenous color mix)
- Frost filter
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Integrated show programs
- Direct color selection for 27 preset colors
- Can be operated in 2; 3; 6-1; 6-2; 12 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control; master/slave function; QuickDMX
- Flicker-free
- With a beam angle of 15°
- Variable color temperature 2700 K - 8000 K
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units

Logistic

EAN / GTIN: 4026397689259

Weight: 37,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.60 m

Bulky product

- Suitable for outdoor use IP65
- For application areas such as: Architecture; stage; wedding/gala/events; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand

ROADINGER Flightcase 2x TMH-30/40/60 with wheels

PRO flightcase with castors for 2 x TMH-30/TMH-40/TMH-60

- Developed for 51785980 EUROLITE LED TMH-30 Moving-Head Spot COB, 51785996 EUROLITE LED TMH-40 Moving-Head Wash, 51785984 EUROLITE LED TMH-60 Moving-Head Spot COB or comparable Moving Heads
- Suitable for 2 units
- Interior and cover (not removable) upholstered with foam
- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, medium-sized steel ball corners (chrome)
- 4 castors (100 mm), 2 of which with locking brakes
- 4 stacking dishes for stacking the cases
- 2 hinges
- 2 high-quality butterfly locks
- 2 chrome case handles
- For perfect protection
- Castors
- Branded hardware
- Made in Europe

Technical specifications:

Weight:	31.70 kg
---------	----------

EUROLITE AKKU IP PAR 14 HCL QuickDMX

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Battery/battery pack built-in Via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	IP T-Con (F) mounting version
Battery pack type:	1 x lithium ion 22.2 V, 4400 mAh, 97.68 Wh
Battery pack:	Battery operation up to 26h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED type:	14 x 10 W 6in1 RGBWA/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
Equipment:	Frost filter
DMX channels:	2; 3; 6-1; 6-2; 12
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP

Cooling:	Passive convection cooling
Control:	DMX; stand-alone; IR remote control; master/slave function; QuickDMX
Fixtures available for:	LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle:	15°
Beam angle (1/2 peak):	15° 27° 30° 60°
Color temperature:	2700K - 8000K adjustable
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 31.7 cm Depth: 22.7 cm Height: 37.0 cm
Weight:	7.85 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

ROADINGER Flightcase 2x TMH-30/40/60 with wheels

Maximum load:	50 kg
Transport aid:	Castors
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	25.5 cm x 31 cm x 31 cm
Accessory compartment:	11.5 cm x 31 cm x 31 cm
Inside dimensions:	67 cm x 31 cm x 31 cm
Dimensions:	Width: 71 cm Depth: 35 cm Height: 53 cm
Weight:	16.00 kg

Scope of delivery:

1 x spotlight
 1 x power cord
 1 x XLR cable
 3 x frost filter
 1 x remote control
 2 x screw
 1 x user manual