



### Features:

#### EUROLITE AKKU IP PAR 14 HCL QuickDMX

IP65 battery-powered spotlight with RGBWA+UV LEDs, QuickDMX, frost filter and IR remote control

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 26h depending on program used
- 14 LEDs 10 W 6in1 RGBWA/UV (homogenous color mix)
- Frost filter
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Integrated show programs
- Direct color selection for 27 preset colors
- Can be operated in 2; 3; 6-1; 6-2; 12 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control; master/slave function; QuickDMX
- Flicker-free
- With a beam angle of 15°
- Variable color temperature 2700 K - 8000 K
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units

### Logistic

EAN / GTIN: 4026397689259

Weight: 37,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.60 m

Bulky product

- Suitable for outdoor use IP65
- For application areas such as: Architecture; stage; wedding/gala/events; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand

#### **ROADINGER Flightcase 2x TMH-30/40/60 with wheels**

PRO flightcase with castors for 2 x TMH-30/TMH-40/TMH-60

- Developed for 51785980 EUROLITE LED TMH-30 Moving-Head Spot COB, 51785996 EUROLITE LED TMH-40 Moving-Head Wash, 51785984 EUROLITE LED TMH-60 Moving-Head Spot COB or comparable Moving Heads
- Suitable for 2 units
- Interior and cover (not removable) upholstered with foam
- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, medium-sized steel ball corners (chrome)
- 4 castors (100 mm), 2 of which with locking brakes
- 4 stacking dishes for stacking the cases
- 2 hinges
- 2 high-quality butterfly locks
- 2 chrome case handles
- For perfect protection
- Castors
- Branded hardware
- Made in Europe

#### **Technical specifications:**

|         |          |
|---------|----------|
| Weight: | 31.70 kg |
|---------|----------|

#### **EUROLITE AKKU IP PAR 14 HCL QuickDMX**

|                    |                                                                                                                  |
|--------------------|------------------------------------------------------------------------------------------------------------------|
| Power supply:      | 100-240 V AC, 50/60 Hz                                                                                           |
| IP classification: | IP65                                                                                                             |
| Protection class:  | Protection class I                                                                                               |
| Power connection:  | Battery/battery pack built-in<br>Via IP T-Con (M) mounting version power supply cord with safety plug (provided) |
| Power output:      | IP T-Con (F) mounting version                                                                                    |
| Battery pack type: | 1 x lithium ion 22.2 V, 4400 mAh, 97.68 Wh                                                                       |
| Battery pack:      | Battery operation up to 26h depending on program used<br>Recharging time 3h                                      |
| Lamp type:         | LED lamp                                                                                                         |
| LED type:          | 14 x 10 W 6in1 RGBWA/UV (homogenous color mix)                                                                   |
| Flash rate:        | 0 - 20 Hz                                                                                                        |
| Equipment:         | Frost filter                                                                                                     |
| DMX channels:      | 2; 3; 6-1; 6-2; 12                                                                                               |
| DMX input:         | 3-pin XLR (M) mounting version IP                                                                                |
| DMX output:        | 3-pin XLR (F) mounting version IP                                                                                |

|                         |                                                                                                                            |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Cooling:                | Passive convection cooling                                                                                                 |
| Control:                | DMX; stand-alone; IR remote control; master/slave function; QuickDMX                                                       |
| Fixtures available for: | LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief |
| Projection:             | Flicker-free                                                                                                               |
| Carrier frequency:      | 2.4 GHz                                                                                                                    |
| Beam angle:             | 15°                                                                                                                        |
| Beam angle (1/2 peak):  | 15°<br>27°<br>30°<br>60°                                                                                                   |
| Color temperature:      | 2700K - 8000K adjustable                                                                                                   |
| Housing color:          | Black                                                                                                                      |
| Attachment system:      | Double bracket                                                                                                             |
| Display type:           | LCD display                                                                                                                |
| Material:               | Aluminum casting                                                                                                           |
| Dimensions:             | Width: 31.7 cm<br>Depth: 22.7 cm<br>Height: 37.0 cm                                                                        |
| Weight:                 | 7.85 kg                                                                                                                    |
| Noise classification:   | Class 0 (no noise at all)                                                                                                  |
| Battery:                | 1 x button cell 3.0 V CR2032 lithium manganese built-in                                                                    |

#### ROADINGER Flightcase 2x TMH-30/40/60 with wheels

|                         |                                               |
|-------------------------|-----------------------------------------------|
| Maximum load:           | 50 kg                                         |
| Transport aid:          | Castors                                       |
| Use of brands:          | Branded hardware                              |
| Material:               | Birch multiplex, 7 mm                         |
| Color:                  | Dark brown, laminated                         |
| Compartment dimensions: | 25.5 cm x 31 cm x 31 cm                       |
| Accessory compartment:  | 11.5 cm x 31 cm x 31 cm                       |
| Inside dimensions:      | 67 cm x 31 cm x 31 cm                         |
| Dimensions:             | Width: 71 cm<br>Depth: 35 cm<br>Height: 53 cm |
| Weight:                 | 16.00 kg                                      |

#### Scope of delivery:

1 x spotlight  
 1 x power cord  
 1 x XLR cable  
 3 x frost filter  
 1 x remote control  
 2 x screw  
 1 x user manual