

EUROLITE Set DIY LED THA-20PC TRC + Multi adapter, 3 phases, black

DIY set for connection to 3-phase track systems

Art. No.: 20000830

GTIN: 4026397689310



Features:

- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- Two additional frost filters provide a soft, homogeneous light
- Very high color rendering index (CRI)
- Silent operation
- With a beam angle of 17°
- Flicker-free
- 1 LED 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
- Dimmer electronic
- Control via stand-alone
- With mounting bracket
- The device is cooled by passive convection cooling
- For application areas such as: Decoration; wedding/gala/events; video and photography; advertisement/Shop window; restaurants, bars and hotels
- Application possibility: Suspended; on stand
- <p>EUTRAC Multi adapter, 3 phases, black
- **Multi adapter with data bus option**
- For 3~ circuit track
- Prepared for data bus contacts (data bus contact with SELV safety chip, part no. 99-698-0)
- Screw termination, approved for 6 A inductive / 6 A ohmic up to 250 V
- With earth contact, circuit selection by turnkey switch and optional neutral position during operation
- Due to double mechanical locking perfect track fixing even when using heavy spotlights
- Maximum load up to 5 kg, or 10 kg when using retaining collar 99-066-x
- Made in Germany

Logistic

EAN / GTIN: 4026397689310

Weight: 3,50 kg

Length: 0.41 m

Width: 0.31 m

Height: 0.28 m

Technical specifications:

Weight:	2.29 kg
---------	---------

EUROLITE LED THA-20PC TRC Theater Spot bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	22 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
Cooling:	Passive convection cooling
Control:	Stand-alone
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17° Frost filter 19° Frost filter 26°
Beam angle (1/10 peak):	36° Frost filter 40° Frost filter 53°
Color temperature:	3000K
Color rendering index (CRI):	92 Ra
Illuminance in Lux (lx):	Warm white (WW) 3m: 727 lx, 6m: 188 lx
Housing color:	Black
Attachment system:	Mounting bracket
Transport aid:	Rubber feet
Material:	Aluminum casting
Slot for spot length:	10 cm x 10 cm
Dimensions:	Length: 21.5 cm Width: 14.5 cm Depth: 21 cm
Weight:	2.23 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	1 x Ø10mm
Material:	Metal, 3 mm
Cable construction:	3 x 0.75 mm² H05VV-F
Cable length:	Approx. 1 m
Material:	Aluminum, 1 mm; metal
Ring diameter:	Outside: 99 mm

	Inside: 80 mm
Diameter mounting holes:	1 x Ø4mm
Material:	Aluminum, 0.8 mm
Dimensions:	Width: 9.9 cm Height: 9.9 cm Diameter: Ø 8 cm
Material:	Plastic
Dimensions:	Width: 0.2 cm Diameter: Ø 8 cm
Material:	Aluminum, 1 mm
Dimensions:	Depth: 1.3 cm Diameter: Ø 8.2 cm
Material:	Metal, 2 mm

EUTRAC Multi adapter, 3 phases, black

Power connection:	Mains input via special connector recessed mounting
Power output:	Screw terminal
Weight:	0.05 kg

EUTRAC Retaining collar for multi adapter Ø10,5mm/ Ø13,5mm black

Weight:	0.01 kg
---------	---------

Scope of delivery:

1 x EUROLITE LED THA-20PC TRC Theater Spot bk

1 x spotlight
 1 x barndoor
 1 x filter frame
 2 x frost filter
 1 x ring
 2 x lamp clamping ring
 1 x user manual

1 x EUTRAC Retaining collar for multi adapter Ø10,5mm/ Ø13,5mm black

1 x screwing