

EUROLITE Set DIY LED THA-40PC TRC + Multi adapter, 3 phases, black

DIY set for connection to 3-phase track systems

Art. No.: 20000831

GTIN: 4026397689327



The article is no longer in our assortment.

Features:

- Silent operation
- Very high color rendering index (CRI)
- Flicker-free
- Control via stand-alone; rotary dial for brightness; Dimmer
- 1 LED 57 W COB (chip-on-board) warm white (WW)
- Dimmer electronic
- The device is cooled by passive convection cooling
- Rugged metal housing
- With mounting bracket
- For application areas such as: Decoration; Trade fair and shop fitting; restaurants, bars and hotels; video and photography; advertisement/Shop window
- With a beam angle of 12° - 47°
- <p>EUTRAC Multi adapter, 3 phases, black
- **Multi adapter with data bus option**
- For 3~ circuit track
- Prepared for data bus contacts (data bus contact with SELV safety chip, part no. 99-698-0)
- Screw termination, approved for 6 A inductive / 6 A ohmic up to 250 V
- With earth contact, circuit selection by turnkey switch and optional neutral position during operation
- Due to double mechanical locking perfect track fixing even when using heavy spotlights
- Maximum load up to 5 kg, or 10 kg when using retaining collar 99-066-x
- Made in Germany

Logistic

EAN / GTIN: 4026397689327

Weight: 3,50 kg

Length: 0.41 m

Width: 0.31 m

Height: 0.28 m

Technical specifications:

Weight:	3.88 kg
---------	---------

EUROLITE LED THA-40PC TRC Theater Spot bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	40 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 57 W COB (chip-on-board) warm white (WW)
Cooling:	Passive convection cooling
Control:	Stand-alone; rotary dial for brightness; Dimmer
Projection:	Flicker-free
Beam angle:	12° - 47°
Beam angle (1/2 peak):	12 - 36°
Beam angle (1/10 peak):	18 - 47°
Color temperature:	3100K
Color rendering index (CRI):	92 Ra
Illuminance in Lux (lx):	Narrow 3m: 2008 lx, 6m: 514 lx Wide 3m: 482 lx, 6m: 141 lx
Housing color:	Black
Attachment system:	Mounting bracket
Transport aid:	Rubber feet
Material:	Aluminum casting
Slot for spot length:	13.1 cm x 13.1 cm
Dimensions:	Length: 26 cm Width: 20 cm Depth: 25 cm
Weight:	3.82 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	1 x Ø10mm; 2 x Ø6mm
Material:	Metal, 3 mm
Cable construction:	3 x 0.75 mm² H05VV-F
Cable length:	Approx. 1 m
Material:	Aluminum, 1.5 mm; metal
Ring diameter:	Outside: 12.9 mm Inside: 10.9 mm
Diameter mounting holes:	1 x Ø4mm
Shape:	Octagonal

Material:	Aluminum, 0.8 mm
Dimensions:	Width: 13 cm Height: 13 cm Diameter: Ø 10.5 cm

EUTRAC Multi adapter, 3 phases, black

Power connection:	Mains input via special connector recessed mounting
Power output:	Screw terminal
Weight:	0.05 kg

EUTRAC Retaining collar for multi adapter Ø10,5mm/ Ø13,5mm black

Weight:	0.01 kg
---------	---------

Scope of delivery:

1 x EUROLITE LED THA-40PC TRC Theater Spot bk

1 x spotlight
1 x barndoor
1 x filter frame
1 x user manual

1 x EUTRAC Retaining collar for multi adapter Ø10,5mm/ Ø13,5mm black

1 x screwing