

EUROLITE Set 2x LED SLS-7 HCL Floor + LED QDF-Bar RGBAW Light set Art. No.: 20000833

2x flat spotlight with RGBAW+UV color mixing incl. spotlight bar with 4 LED heads

GTIN: 4026397689341



The article is no longer in our assortment.

Features:

- Slim design for space-saving applications
- Enjoy perfect solid and pastel colors plus ultra violet thanks to 6-color mixing
- DMX and power terminals intelligently designed for easy wiring
- 7 LEDs 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- 2 integrated show programs
- Direct color selection for 19 preset colors
- Can be operated in 2; 3; 4; 6; 10 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control
- Flicker-free
- With a beam angle of 17°
- With double bracket
- Monochrome 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- Available in various colors
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; advertisement/Shop window
- Application possibility: Standing; suspended; on stand
- <p>EUROLITE LED QDF-Bar RGBAW Light Set
- **LED bar with 4 LED heads, LEDs in RGBWA and DMX**
- Crossbar with integrated DMX control unit and stand sleeve
- Ultra-light ideally suited for mobile use

Logistic

EAN / GTIN: 4026397689341
 Weight: 10,40 kg
 Length: 1.30 m
 Width: 0.50 m
 Height: 0.30 m
 Bulky product

- Ideal for bands, stages or solo entertainers
- Suited for installation on a speaker stand (not included) or truss
- Comes pre-assembled with practical transport bag
- Equipped with 240 LEDs (5 mm) in the colors red, green, blue, amber and white
- Movable and tiltable spotlights
- Via DMX, each spot can be individually controlled
- DMX-controlled operation or stand-alone operation
- DMX512 control via any commercial DMX controller (occupies 23 channels)
- Functions: Effect/color presets, built-in programs, strobe effect with variable speed, Master/Slave operation
- Addressing and setting via control panel with 4-digit LED display
- Additional controlling possibility via the EUROLITE IR-7 remote control, included in delivery
- Black lacquered metal version
- IEC terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 240 LEDs 5 mm R/G/B/W/A
 LEDs controlled separately
- Can be operated in 4; 7; 23 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone
- Flicker-free
- Silent operation

Technical specifications:

Weight:	8.11 kg
---------	---------

EUROLITE LED SLS-7 HCL Floor

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 0.5 A fuse replaceable
Lamp type:	LED lamp
LED type:	7 x 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 3; 4; 6; 10
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control
Fixtures available for:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	17°

Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	39°
Wavelength:	Ultra violet (UV) 400 nm
Housing color:	Black
Attachment system:	Double bracket
Display type:	Monochrome 4 digit 7-segment LED display
Transport aid:	Rubber feet
Material:	ABS Acrylonitrile butadiene styrene; metal
Dimensions:	Width: 22 cm Depth: 11 cm Height: 21 cm
Weight:	1.38 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Cable construction:	3 x 0.75 mm² H05VV-F
Cable length:	Approx. 1.2 m
Diameter mounting holes:	5 x Ø11mm
Material:	Metal, 2 mm
Color:	Black
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

EUROLITE LED QDF-Bar RGBAW Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	F 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	240 x 5 mm R/G/B/W/A
Flash rate:	0 - 20 Hz
DMX channels:	4; 7; 23
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone
Fixtures available for:	Light´J; LED PC-Control 512
Projection:	Flicker-free
Housing color:	Black
Dimensions:	Width: 85 cm Depth: 11 cm Height: 36 cm
Weight:	4.5 kg

Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

2 x EUROLITE LED SLS-7 HCL Floor

- 1 x light effect
- 1 x power cord
- 1 x remote control
- 1 x user manual

1 x EUROLITE LED QDF-Bar RGBAW Light Set

- 1 x spotlight
- 1 x remote control