

## EUROLITE Set 4x LED CBB-2 WW/CW Fairlight + Case

Art. No.: 20000838

GTIN: 4026397625578



### Features:

#### EUROLITE LED CBB-2 WW/CW Fairlight

LED light effect bar with WW/CW COB LEDs, incl. IR remote control

- 2 LEDs 50 W COB (chip-on-board) 2in1 CW/WW (homogenous color mix)
- Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 27 preset colors
- Can be operated in 2; 3; 4; 6 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; quick select potentiometer for brightness and color temperature; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 40°
- Variable color temperature 2400 K - 5000 K
- Very high color rendering index (CRI)
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units

### Logistic

EAN / GTIN: 4026397625578

Weight: 26,90 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.34 m

Bulky product

- For application areas such as: Stage; Trade fair and shop fitting; theater; video and photography

#### ROADINGER Flightcase 4x LED CBB-2WW/CW fairlight

- High-quality workmanship with birch multiplex 6.5 mm, dark brown, laminated
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### Technical specifications:

|         |          |
|---------|----------|
| Weight: | 25.07 kg |
|---------|----------|

#### EUROLITE LED CBB-2 WW/CW Fairlight

|                              |                                                                                                                                                                                                                                                                               |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:                | 100-240 V AC, 50/60 Hz                                                                                                                                                                                                                                                        |
| Power consumption:           | 80 W                                                                                                                                                                                                                                                                          |
| Protection class:            | Protection class I                                                                                                                                                                                                                                                            |
| Lamp type:                   | LED lamp                                                                                                                                                                                                                                                                      |
| LED type:                    | 2 x 50 W COB (chip-on-board) 2in1 CW/WW (homogenous color mix)                                                                                                                                                                                                                |
| Flash rate:                  | 0 - 20 Hz                                                                                                                                                                                                                                                                     |
| DMX channels:                | 2; 3; 4; 6                                                                                                                                                                                                                                                                    |
| DMX input:                   | 3-pin XLR (M) mounting version                                                                                                                                                                                                                                                |
| DMX output:                  | 3-pin XLR (F) mounting version                                                                                                                                                                                                                                                |
| Cooling:                     | 1 x cooling fan                                                                                                                                                                                                                                                               |
| Control:                     | Stand-alone; DMX; IR remote control; quick select potentiometer for brightness and color temperature; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for:      | Light Captain; Colorchief                                                                                                                                                                                                                                                     |
| Projection:                  | Flicker-free                                                                                                                                                                                                                                                                  |
| Beam angle:                  | 40°                                                                                                                                                                                                                                                                           |
| Beam angle (1/2 peak):       | 40°                                                                                                                                                                                                                                                                           |
| Beam angle (1/10 peak):      | 75°                                                                                                                                                                                                                                                                           |
| Color temperature:           | 2400K - 5000K adjustable                                                                                                                                                                                                                                                      |
| Color rendering index (CRI): | 94 Ra                                                                                                                                                                                                                                                                         |
| Illuminance in Lux (lx):     | Warm white (WW) 1m: 928 lx, 3m: 123 lx, 6m: 36 lx<br>Cold white (CW) 1m: 1662 lx, 3m: 220 lx, 6m: 65 lx<br>All 1m: 2522 lx, 3m: 331 lx, 6m: 97 lx                                                                                                                             |
| Housing color:               | Black                                                                                                                                                                                                                                                                         |
| Attachment system:           | Mounting bracket                                                                                                                                                                                                                                                              |
| Display type:                | 4 digit 7-segment LED display                                                                                                                                                                                                                                                 |

|                          |                                                         |
|--------------------------|---------------------------------------------------------|
| Material:                | Metal; aluminum casting; plastic                        |
| Dimensions:              | Width: 26.6 cm<br>Depth: 16.95 cm<br>Height: 19.4 cm    |
| Weight:                  | 3.57 kg                                                 |
| Noise classification:    | Class 2 (slight noise)                                  |
| Photobiological safety:  | Risk Group 0                                            |
| Cable construction:      | 3 x 1.0 mm² H05RN-F                                     |
| Cable length:            | Approx. 1.2 m                                           |
| Battery:                 | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Material:                | Metal, 0.8 mm                                           |
| Diameter mounting holes: | 1 x Ø11mm; 2 x Ø8mm                                     |
| Material:                | Metal, 2.5 mm                                           |

**ROADINGER Flightcase 4x LED CBB-2WW/CW fairlight**

|                        |                         |
|------------------------|-------------------------|
| Maximum load:          | 50 kg                   |
| Use of brands:         | Branded hardware        |
| Material:              | Birch multiplex, 6.5 mm |
| Color:                 | Dark brown, laminated   |
| Device compartment:    | 28 cm x 15.5 cm x 24 cm |
| Inside dimensions:     | 66.5 cm x 35 cm x 24 cm |
| Accessory compartment: | 10.5 cm x 35 cm x 24 cm |
| Weight:                | 10.80 kg                |

**Scope of delivery:**

- 1 x spotlight
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x user manual